

Location: _____




R1200-JC

**LARGE SUMP ROOF DRAIN WITH STAINLESS
STEEL 6" HIGH BALLAST GUARD FOR IRMA ROOFS**

Specification: MIFAB® Series R1200-JC lacquered cast iron deep sump roof drain with 15" diameter anchor flange, large cast iron waterproofing membrane clamp ring with integral gravel stop, 6" (152) high stainless steel perforated ballast guard with ½" (13) round drainage openings and standard self-locking polyethylene dome strainer with a free area of 125 square inches.

Function: For roofs that use the insulated membrane assembly method of waterproofing (I.R.M.A.). Typical when built-up felt and asphalt waterproofing is installed on top of the roof membrane for protection against the elements. The ballast guard is furnished to retain the crushed gravel used in flat roof construction. The slots allow for drainage without clogging. Large free area dome provides for efficient drainage of rain water and prevents debris from entering the drain line. Extra wide anchor flange and membrane clamp with tongue in groove design provides for secure grip of membrane and roof flashing materials.



Deck opening - 10" (254) with sump receiver - 15 3/4" (400)

PIPE SIZE	BODY HEIGHT				
	NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC (-30) / ABS (-31)
○ 2" (51)	□ 5 3/4" (146)	□ 5 1/2" (140)	□ 6 1/2" (165)	□ 6 1/2" (165)	□ 6 3/4" (171)
○ 3" (76)	□ 5 3/4" (146)	□ 5 1/2" (140)	□ 6 5/8" (168)	□ 6 1/2" (165)	□ 7 1/2" (191)
○ 4" (102)	□ 5 3/4" (146)	□ 5 1/2" (140)	□ 5 1/2" (140)	□ 6 1/2" (165)	□ 7 5/8" (194)
○ 5" (127)	□ 5 3/4" (146)	□ 5 1/2" (140)	□ 6 5/8" (168)	□ 6 3/4" (171)	-
○ 6" (152)	□ 7 1/4" (184)	□ 5 5/8" (143)	□ 5 5/8" (143)	□ 6 1/2" (165)	-
○ 8" (203)	□ 5 7/8" (149)	□ N/A	□ N/A	□ (A7-8X body)	-

SUFFIX	OPTIONAL VARIATIONS
□ -6	Vandal proof dome (metal dome only)
□ -11	Acid resistant epoxy coating
□ -12	Galvanized metal dome
□ -12A	Galvanized body and membrane clamp
□ -12B	Galvanized metal dome and membrane clamp
□ -13	Galvanized body, membrane clamp and dome
□ -14	Flat grate (replaces dome strainer)
□ -28	Stainless steel body (Type 304) (2", 3", 4")
□ -30	PVC socket connection body
□ -31	ABS socket connection body
□ -81	Rough bronze dome
□ -83	Stainless steel mesh screen over dome
□ -90	Threaded side outlet (2", 3", 4")
□ -90NH	No Hub side outlet (cast iron only) (2", 3", 4")
□ (Standard)	No hub outlet
□ -B	Sump receiver
□ -BA	Buy America Act compliant product
□ -F1, -F2, -F3	Accuflow (parabolic weir) specify

SUFFIX	OPTIONAL VARIATIONS
□ -G	Stainless steel ballast guard
□ -M	Metal dome
□ -M-80	Low profile silhouette aluminum dome
□ -P	Push on outlet
□ -PA	Pennsylvania Steel Act compliant product
□ -R	2" external water dam
□ -T	Threaded outlet (2", 3", 4")
□ -U	Underdeck clamp
□ -U3	Underdeck clamp with cutaway side
□ -W	Adjustable water dam
□ -W-1	Water proofing flange
□ -W2	2" internal water dam
□ -W3	3" internal water dam
□ -W4	4" internal water dam
□ -W6	6" diameter adjustable water dam
□ -X	Inside caulk outlet (2", 3", 4")
□ -XJ	Vertical expansion joint (see R1900)

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____ Page No: _____
Section No: _____ Contractor: _____
Schedule No: _____ Purchase Order No: _____