



Location: **MIFAB®****F1330C****FLOOR DRAIN WITH 9" ROUND TRACTOR GRATE AND DEEP SUMP**

Specification: MIFAB Series F1330C lacquered cast iron floor drain with anchor flange, cast iron clamp ring with primary and secondary weepholes for waterproofing membrane, adjustable collar with deep sump body, and standard 1" (25) thick, 9" (235) round, (specify material finish) tractor grate.


Function: Used in warehouses, mechanical rooms, parking garages and other membrane finished areas. 9" Round, adjustable tractor grate is used with all types of poured finished floors. Membrane clamp is provided to secure the waterproofing membrane. Deep sump body provides capacity for heavy water flow.

**PARTS:**

A2 Body

F1320-TA-4 (*)
(*) Denotes Strainer Finish (-1, -3 or -4)

A2-C3-W



HS-1

STRAINER DIAMETER	STRAINER ADJUSTMENT		FREE AREA	ANSI/ASME RATING		PIPE SIZE	BODY HEIGHT				
	MIN	MAX		LOAD RATING			NO HUB (STANDARD)	PUSH ON (P)	THREADED (T)	INSIDE CAULK (X)	PVC/ABS (-30)/(-31)
9" (235)	2" (51)	2 7/8" (73)	18 in ² (11,613 ²)	ANSI/ASME LOAD CLASS "SPECIAL DUTY" (OVER 10,000 LBS.)		2" (51) ○ 3" (76) ○ 4" (102) ○ 5" (127) ○ 6" (152) ○	6" (152) ☐ 6" (152) ☐ 6" (152) ☐ 6" (152) ☐ 7 1/4" (184) ☐	6 1/8" (156) ☐ 6 1/8" (156) ☐ 6 1/8" (156) ☐ — ☐ 7" (178) ☐	5 7/16" (138) ☐ 5 7/16" (138) ☐ 5 7/16" (138) ☐ 5 7/16" (138) ☐ 7" (178) ☐	6 1/4" (159) ☐ 6 1/4" (159) ☐ 6 1/4" (159) ☐ 6 1/4" (159) ☐ 6 1/4" (159) ☐	7 1/8" (181) ☐ 7 3/8" (187) ☐ 7 3/8" (187) ☐ — ☐ — ☐

SUFFIX

- ☐ -1 Nickel bronze (vener)
- ☐ -3 Stainless steel (vener)
- ☐ -4 Ductile iron grate
- ☐ -5 Sediment bucket
- ☐ -6 Security screws (TR30 Torx & pin)
- ☐ -7 1/2" trap seal primer connection
- ☐ -8 Backwater valve (2", 3", 4")
- ☐ -11 Acid resistant epoxy coated body
- ☐ -12 Galvanized top assembly
- ☐ -13 Galvanized body
- ☐ -15 Extension
- ☐ -16 Square top
- ☐ -21 Secondary flat stainless steel strainer (2", 3", 4")

SUFFIX

- ☐ -24 Solid secured cover
- ☐ -28 Stainless steel body (Type 304)
- ☐ -30 PVC socket connection body
- ☐ -31 ABS socket connection body
- ☐ -34 Closure plug
- ☐ -35 Stainless steel mesh over bucket
- ☐ -40 Underdeck clamp
- ☐ -41 Sump receiver
- ☐ -50 Lacquered cast iron funnel
- ☐ -90 Threaded side outlet (2", 3", 4") (cast iron only)
- ☐ -90NH No hub side outlet (2", 3", 4") (cast iron only)
- ☐ -95 Client logo
- ☐ -ARRA ARRA (Stimulus Act) compliant product

SUFFIX

- ☐ -BA Buy American Act compliant product
- ☐ -F4 4" Round funnel
- ☐ -F6 6" Round funnel
- ☐ -G Oval 4" x 9" funnel
- ☐ -HP Heel proof grate (1/4" maximum grate opening size, -3 and -4 only, veneer)
- ☐ -J 6" x 3" x 1" funnel
- ☐ (Standard) No hub outlet
- ☐ P Push on outlet
- ☐ -PA Pennsylvania Steel Act compliant product
- ☐ T Threaded outlet
- ☐ X Inside caulk outlet
- ☐ -Z Extended wide elastomeric flange

Job Name:
 Section No:
 Schedule No:

Page No:
 Contractor:
 Purchase Order No: