

R454b Refrigerant

SUBMITTAL DATA SHEET



Series Name: Extreme Heat AHU Series
Model Number: MAUHE-H24B-2A/MO1HE-H24B-2A

Air Handler Heat Pump System

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



INDOOR SPECIFICATION

ESP(in.W.G)	0-0.8
Indoor Noise Level (Turbo/H/M/L/Si) (dBA)	44 / 44 / 42 / 28 / 28
Dimension (W×D×H)	inch 17-1/2 x 21 x 45 mm 445 x 534 x 1143
Package (W×D×H)	inch 20-7/8 x 26-1/2 x 48-5/8 mm 530 x 675 x 1235
Net/Gross Weight	lbs 106 /127 kg 47.9 / 57.8

OUTDOOR SPECIFICATION

Compressor Type	ROTARY
Compressor Model	KTM240D46UKT2
Refrigerant	R454B
Refrigerant Oil Charge(mL)	620
Refrigerant Oil	VG74
Outdoor Air Flow (Max) (CFM)	1,766
Outdoor Noise Level (dBA)	60
Dimension (W×D×H)	inch 35 x 13-1/2 x 26-1/2 mm 890 x 342 x 673
Package (W×D×H)	inch 39-1/8 x 15-5/8 x 29-1/8 mm 995 x 398 x 740
Net/Gross Weight	lbs 102 /109 kg 46.4 / 49.5

EFFICIENCY

Cooling	Heating
SEER2	HSPF2-4
18.3	10.0
EER2	COP
11.7	3.33

PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	23,000
Min/Max Capacity	7,200 ~ 2,7000
Moisture Removal(L/h)	2.05
Standard Operating Range(*F/*C)	-22~122 (-30 ~ 50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

PERFORMANCE of Heating



Heating (Btu/hr)	
1. @ 47°F Rated	24,000
2. @ 47°F Min/Max Capacity	7,100 ~ 30,000
3. @ 17°F Rated	20,000
4. @ 5°F Rated: Capacity / COP	21,600 /1.87
5. @ 5°F Max: Capacity	21,600
Standard Operating Range(*F/*C)	-22~75 (-30 ~ 24)
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Heating Conditions, Compressor Operating at Max. Frequency	Indoor: 70°F DB/60°F WB Outdoor: 5°F DB/5°F WB

ELECTRICAL

Indoor Power Supply	115/208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	5.5/4.0
Indoor MOP	15.0
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	19.0
Outdoor MOP	20.0
Communication Wiring	AWG 20/2
Compressor RLA	14.0
Outdoor Fan Motor RLA	1.0
Outdoor Fan Motor W	80
Indoor Fan Motor RLA	3.0
Indoor Fan Motor W	250
System Power Input @ Cooling (W)	1,965 (530 ~ 2,870)
System Power Input @ Heating (W)	2,112 (440 ~ 2,730)
MCA: Min. circuit amps (A)	MOCP: Max. over current protection (A)
RLA: Rated load amps (A)	W: Fan motor rated output (W)


PIPING

Throttle type(Indoor)	EXV
Throttle type(Outdoor)	EXV
Liquid Size	3/8" (9.52mm)
Gas Size	3/4" (19mm)
Max. Piping Length(ft/m)	164 (50)
Max. Height Difference(ft/m)	82 (25)
Max. Pre-charged Length(ft/m)	25 (7.5)
Refrigerant Pre-charged Amount(oz/kg)	74 (2.1)
Additional Charge of Refrigerant(oz/ft)/(g/m)	0.7 (65)
Connection Method	Flared




Outdoor Unit Dimension


Unit:inch(mm)



Installation Instruction For Outdoor Unit



Fan Performance For Indoor Unit



Features

- Multi-position installation: horizontal(left or right), vertical(up or down)
- Aluminum Coil
- Constantly Air Flow system up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 25kW
- Easy Maintenance
- Multiple control options available:
 - Two way communication wired controller:120N(X6)
 - Two way communication wired controller with built-in WiFi:120N(X6W)
 - Wireless remote controller
 - Third-Party 24V Thermostat
- Adaptive Control System
- High efficiency up to 19 SEER2, 12.5 EER2, 10.3 HSPF2
- 100% heat output at -4F*
- Chassis heater and crankcase heater equipped as standard

* For 36K model, rated cooling capacity/heating capacity at -4F=100%