



BETTER FIT.
BETTER PROTECTION.

EN388
CE
3242B



EN388 STANDARDS						
Abrasion	1	2	3	4	–	–
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	–	–
Puncture	1	2	3	4	–	–
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™ Touch
Screen Compatible
Fingertips

Reinforced
Nitrile Coating

Polyurethane
Better fit



Light and
Breathable Back

Color-Coded Bands
Easy cut level
identification

SPECIFICATIONS		RECOMMENDED APPLICATIONS	CARE INSTRUCTIONS
Gauge	15		
Liner Material	Polyester and HPPE Blend Knit	■ Light Demolition ■ Light Material Handling ■ General Work ■ High-Dexterity Applications ■ Wire Stripping	Machine wash warm water (105°F), mild detergent, no bleach. Line dry.
Dip Material	Polyurethane		
Cuff Style	Elasticated Knit		

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8920	48-73-8920B
M	48-73-8921	48-73-8921B
L	48-73-8922	48-73-8922B
XL	48-73-8923	48-73-8923B
XXL	48-73-8924	48-73-8924B

SEE
MORE
PPE



or visit <https://qr.mke.lt/2qm6s>

