

HIGH VISIBILITY CUT LEVEL 3

POLYURETHANE DIPPED GLOVES

BETTER FIT.

BETTER PROTECTION.

EN388



4342C



EN388 STANDARDS						
Abrasion	1	2	3	4	–	–
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	–	–
Puncture	1	2	3	4	–	–
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™ Touch Screen Compatible Fingertips

Reinforced Nitrile Coating

Polyurethane Better fit



High Dexterity Fingertips

Light and Breathable Back

Color-Coded Bands Easy cut level identification

SPECIFICATIONS		RECOMMENDED APPLICATIONS	CARE INSTRUCTIONS
Gauge	15	- Demolition - Material Handling - General Work - Wire Stripping - Pipe Threading - Cutting	Machine wash warm water (105°F), mild detergent, no bleach. Line dry.
Liner Material	Polyester and HPPE Blend Knit		
Dip Material	Polyurethane		
Cuff Style	Elasticated Knit		

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8930	48-73-8930B
M	48-73-8931	48-73-8931B
L	48-73-8932	48-73-8932B
XL	48-73-8933	48-73-8933B
XXL	48-73-8934	48-73-8934B

SEE MORE PPE





or visit <https://qr.mke.tt/2qm6s>

