

Features

- Solid brass construction
- Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Swivel spout assembly with integral diverter fitting
- Solid brass pull-out sidespray
- 6.00" (15.2 cm) spout height at outlet
- 9.05" (23.0 cm) spout reach (c-c)
- For 8" (20.3 cm) centers - Maximum 20" (50.8 cm)
- ADA Complaint (Handles Only)
- 1.8 GPM (6.8 LPM) Max

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- NSF/ANSI/CAN 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1 (Handle Only)
- Energy Policy Act of 1992
- California Energy Commission
- ASME A112.18.3 (Back Flow)
- All applicable US Federal and State material regulations

Colors / Finishes

- 10B: Oil Rubbed Bronze
- 15: Polished Nickel
- 15S: Satin Nickel - PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

Specified Model

Model	Description	Colors Finishes				
2470-5433	Two-Handle Kitchen Faucet with Sidespray	☐ 10B	☐ 15	☐ 15S	☐ 26	☐ Other

Product Specification Add "Color / Finish" suffix to Model number, below.

The Two-Handle Kitchen Faucet with Sidespray shall be made of solid brass construction. Faucet shall incorporate a swivel spout assembly with integral sidespray diverter fitting and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.8 gallons (6.8 liters) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 6.00" (15.2 cm) spout height at outlet and a 9.05" (23.0 cm) spout reach (c-c). Faucet shall incorporate lever handles. Two-Handle Kitchen Faucet shall be Newport Brass Model 2470-5433/____.



PRODUCT DIMENSIONS *(Units are in inches)*

Technical drawings of various fire hydrant types and their dimensions. The drawings include side and top views of different hydrant models, showing their components and dimensions in both inches and millimeters.

Dimensions (Inches [Millimeters]):

- 4.00 [101,6] MIN / 10.00 [254,0] MAX
- 3.30 [83,8]
- 2.00 [50,8] AMOUNT OF STEM REQ. FROM DECK
- 1.68 [42,6] MAX DECK THICKNESS
- Ø 2.57 [65,3]
- Ø 1.13 [28,6]
- 3.32 [84,4]
- Ø 2.23 [56,6]
- Ø 1.00 [25,4]
- 1.85 [46,9] MAX DECK THICKNESS
- 2X 1/2 NPSM INLETS
- 2X 1/2 NPSM OUTLETS
- 1/4-18 NPSM
- 4.88 [123,9]
- Ø 2.27 [57,8]
- 2.66 [67,6] MAX DECK THICKNESS
- 6.00 [152,4]
- 10.93 [277,7]
- 9.05 [230]
- 8.32 [211,3]

NEWPORT BRASS®
Flawless Beauty. From Faucet to Finish.™