

Features

- Solid brass construction
- 1/2" NPT spout inlet fitting
- 10.32" (26.2 cm) spout length
- Rough valve incorporates a brass valve body assembly
- Rough valve incorporates quarter-turn washerless ceramic disc valve cartridges
- Intended for use with Newport Brass rough valve as specified (Required Accessory)
- ADA Compliant

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1-18
- IAPMO/cUPC
- IPC
- ADA & ICC/ANSI A117.1
- All applicable US Federal and State material regulations

Colors / Finishes

- 10B: Oil Rubbed Bronze
- 15: Polished Nickel
- 15S: Satin Nickel - PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

Wall-Mounted Tub Trim

3-2475



Specified Model

Model	Description	Colors Finishes				
3-2475	Wall-Mounted Tub Trim	☐ 10B	☐ 15	☐ 15S	☐ 26	☐ Other

Required Accessory

Application	Wall Tub Rough Valve
Description	2-Cartridge Assembly
Inlet/Outlet Size	1/2"
Part Number	1-500U
Image	

Product Specification Add "Color / Finish" suffix to Model number, below.

The Wall-Mounted Tub Trim shall be made of solid brass construction. Wall-Mounted Tub Trim shall include lever handles and a 10.32" (26.2 cm) tub spout that incorporates a 1/2" NPT inlet fitting. Wall-Mounted Tub Trim shall be Newport Brass Model 3-2475/____ and Newport Brass rough valve shall be 1-500U.

Product dimensions are provided for reference only. For specific product installation guidelines, please reference the installation instructions of the product being installed.



t: 949.417.5207 | www.newportbrass.com
©2020 Brasstech, Inc.