

Features

- Solid brass construction
- Brass valve bodies
- Quarter-turn washerless ceramic disc valve cartridges
- Spout assembly with integral supply hoses
- Pop-up drain with tailpiece
- 1.25" (3.2 cm) spout height at outlet
- 4.75" (12.1 cm) spout reach (c-c)
- For 8" (20.3 cm) centers - Maximum 20" (50.8 cm)
- ADA Compliant
- 1.2 GPM (4.5 LPM) Max

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1-18
- IAPMO/cUPC
- NSF/ANSI 61, SECTION 9
- NSF/ANSI 372
- IPC
- ADA & ICC/ANSI A117.1
- Energy Policy Act of 1992
- EPA WaterSense
- California Energy Commission
- All applicable US Federal and State material regulations

Colors / Finishes

- 10B: Oil Rubbed Bronze
- 15: Polished Nickel
- 15S: Satin Nickel - PVD
- 26: Polished Chrome
- Other: Refer to the Newport Brass catalog for additional color/finish options.

Widespread Lavatory Faucet

850



Specified Model

Model	Description	Colors Finishes				
850	Widespread Lavatory Faucet	☐ 10B	☐ 15	☐ 15S	☐ 26	☐ Other

Product Specification Add "Color / Finish" suffix to Model number, below.

The two-handle Widespread Lavatory Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature brass valve bodies with quarter-turn washerless ceramic disc valve cartridges. Faucet shall have a 1.2 gallon (4.5 liter) per minute maximum flow rate. Product shall be for 8" (20.3 cm) centers - Maximum 20" (50.8 cm). Product shall incorporate a 1.25" (3.2 cm) spout height at outlet and a 4.75" (12.1 cm) spout reach (c-c). Faucet shall include a pop-up drain with tailpiece and incorporate ADA compliant traditional lever handles. Widespread Lavatory Faucet shall be Newport Brass Model 850/____.

PRODUCT DIMENSIONS *(Units are in inches)*

Technical drawings of three different fire alarm pull station models, showing dimensions in inches and millimeters.

Model 1 (Left):

- Top mounting bracket width: 4.00 [101.6] MIN, 10.00 [254.0] MAX
- Stem diameter: $\phi 2.35$ [59.7]
- Amount of stem required from deck: 2.50 [63.5]
- Max deck thickness: 1.20 [30.5]
- Stem diameter: $\phi .38$ [9.5]
- Max deck thickness: 2.75 [69.9]

Model 2 (Middle):

- Top mounting bracket width: 4.00 [101.6] MIN, 10.00 [254.0] MAX
- Stem diameter: $\phi 2.34$ [59.4]
- Stem diameter: $\phi 1.00$ [25.4]
- 2X 1/2 NPSM OUTLETS
- 2X 1/2 NPSM INLETS

Model 3 (Right):

- Top mounting bracket width: 5.46 [138.7]
- Stem diameter: $\phi 2.34$ [59.4]
- Stem diameter: $\phi 1.00$ [25.4]
- 2X 1/2 NPSM OUTLETS
- 2X 1/2 NPSM INLETS

t: 949.417.5207 | www.newportbrass.com
©2020 Brasstech, Inc.