



RS RETROFIT RETAINER STRAP, 16 1/2"

CATALOG NUMBER

RS16



CERTIFICATIONS



FEATURES

Ideal for both new and existing applications

Can be installed without disassembly of the hanging system and/or removing the clamp

Compatible with all standard nVent CADDY beam clamps and can be secured to either the set screw or threaded rod

Large teardrop-shaped opening is compatible with multiple threaded rod diameters, reducing inventory by 50%

Coined edge on teardrop-shaped opening locks into rod, eliminating shifting during install

Provides a secure attachment in seismic zones and complies with NFPA® requirements

PRODUCT ATTRIBUTES

Material: Steel

Finish: Pregalvanized

Length: 16 1/2"

Width: 1 3/4"

Thickness: 16 GA

Rod Size: 3/8";1/2";5/8";3/4"


Hole Size: 1 1/8"

A: 3 1/4"

ADDITIONAL PRODUCT DETAILS

Add 2" to width of flange to determine minimum length strap required.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.