



"SOSR STAND OFF TWO HOLE STRAP FOR CPVC PIPE, 1 1/4" PIPE"

CATALOG NUMBER

SOSR125



CERTIFICATIONS



FEATURES

Includes flared edges to protect piping

Rated for use with CPVC fire sprinkler pipe

"Positions pipe 1-1/2" (38 mm) off the mounting surface eliminating the need for wooden spacer blocks"

Can be mounted in both vertical and horizontal positions on concrete, steel and wood

Meets the UL® 203 stringent upward thrust requirement

UL® Listed as both a hanger and pipe restraint

Complies with static load requirements of NFPA® 13

Includes mounting screws

Can be used with 3TW backing nut on composite wood joist installations

PRODUCT ATTRIBUTES

Material: Steel

Finish: Pregalvanized


Pipe Size: 1 1/4"

Hole Size: 0.2"

A: 3 5/16"

B: 3 5/8"
C: 1"
Thickness: 16 ga
Hanger Spacing: 6' Max

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America +1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support	Europe Netherlands: +31 800-0200135 France: +33 800 901 793	Europe Germany: 800 1890272 Other Countries: +31 13 5835404	APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500
---	--	--	--