



Shielded Flex Couplings for DWV & Non-Pressure Transitions

Flexible coupling is manufactured from natural rubber, synthetic rubber or vinyl.

PASCO's 56 Series Flex Couplings with Stainless Steel Shear Rings resist heavy earth loads, shear forces and coupling deterioration caused by environmental effects.

- 300 Series Stainless Steel Clamps and Shear Rings
- Minimum thickness of Shear Ring is .018".
- Torque to 80 lbs.
- Repair existing pipe
- Flex Couplings comply with:
 - ASTM C1173-2002
 - IAPMO 4933

Tough Nut Stainless Steel Clamps and Shear Ring

Clay to Clay

PART NUMBER	SIZE
56144PRC	4"

Straight Through
Equals Fernco 5001 RC Series
Mission MR01 ARC

Clay to Cast Iron/Plastic

PART NUMBER	SIZE
56244PRC	4"

Equals Fernco 5002 RC Series
Mission MR02 ARC

Cast Iron, Plastic or Steel to Cast Iron, Plastic or Steel

PART NUMBER	SIZE
5643PRC	4" x 3"*
5644PRC	4"
5655PRC	5"
5666PRC	6"

Sizes 4" and 5" - Single Nut
Sizes 6" and above - Double Nut
• Straight Through
Equals Fernco 5056 RC Series
Mission MR56 ARC



• Use **PASCO 2SM**