

SLIM LINE®

- 3/8" NPT inlet/outlet
- Available in 5" and 10" lengths
- Pressure relief button
- Mounting bracket included



W385-PR
W38-PRA

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)	Optional Accessories Model #
W385-PR	152007	Gray	Black	3/8" NPT	4½" x 7"	30-125	40-100	WW38
W38-PRA	152005	Gray	Black	3/8" NPT	4½" x 12"	30-125	40-100	WW38

STANDARD

- 3/4" NPT inlet/outlet
- Pressure relief button
- Available with either clear or opaque sump
- Accepts a wide variety of 2½" to 3" diameter cartridges



W34-PR
WC34-PR

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)	Optional Accessories Model #
W34-PR	152047	Gray	Black	3/4" NPT	12¼" x 5 ½"	30-125	40-100	WMB34, WW34
WC34-PR	152018	Clear	Black	3/4" NPT	12¼" x 5 ½"	30-125	40-100	WMB34, WW34

VALVE-IN-HEAD

- Valve-In-Head (VIH) closes both the inlet and outlet port simultaneously making cartridge change-outs quick and easy
- 3/4" NPT inlet/outlet
- Pressure relief button
- Accepts a wide variety of 2½" to 3" diameter cartridges



WVC34



Tested and Certified by NSF International.

COMPONENT

Available in many sizes and styles, our housings are manufactured from durable materials with proven performance, including polypropylene, and clear styrene acrylonitrile.

Model #	Part #	Sump	Cap	I/O	Overall Dimensions	Operating Pressure (psi)	Operating Temperature (deg. F)	Optional Accessories Model #
WVC34	152003	Clear	Black	3/4" NPT	12¼" x 5 ½"	30-125	40-100	WMB34, WW34