

traditional filter housings

A TASTEFUL ADDITION TO ANY HOME

SlimLine®, Standard and Valve-In-Head

American Plumber® filter housings are available in many sizes and styles. Our housings are manufactured from durable materials with proven performance, including polypropylene and clear styrene acrylonitrile.



W38-PR series

- ★ .375" NPT inlet/outlet
- ★ Available in 5" and 10" lengths
- ★ Pressure relief button
- ★ Mounting bracket included

W34-PR series

- ★ .75" NPT inlet/outlet
- ★ Pressure relief button
- ★ Available with either clear or opaque sump
- ★ Accepts a wide variety of 2.5" to 3" diameter cartridges

WVC-34

- ★ Valve-In-Head (VIH) closes both the inlet and outlet port simultaneously making cartridge change-outs quick and easy
- ★ .75" NPT inlet/outlet
- ★ Pressure relief button
- ★ Accepts a wide variety of 2.5" to 3" diameter cartridges

SlimLine® specifications

model #	part #	sump	cap	I/O	overall dimensions	operating pressure (psi)	operating temp (deg. F)	optional accessories model #
W385-PR	152007	gray	black	.375" NPT	4.5" x 7"	30-125	40-100	WW38
W38-PRA	152005	gray	black	.375" QC	4.5" x 12"	30-125	40-100	WW38
W34-PR	152047	gray	black	.75" NPT	12.25" x 5.125"	30-125	40-100	WMB34, WW34
WC34-PR	152018	clear	black	.75" NPT	12.25" x 5.125"	30-125	40-100	WMB34, WW34
WVC34	152003	clear	VIH-black	.75" NPT	12.25" x 5.125"	30-125	40-100	WMB34, WW34



Tested and Certified by NSF International.



American
PLUMBER®

5730 NORTH GLEN PARK ROAD
MILWAUKEE, WISCONSIN 53209
Phone 800.645.5428 • Fax 888.588.9388
www.americanplumber.com