

SEDIMENT cartridges

Spun Polypropylene



W5P
W25P

- Whole-House filter cartridges
- Manufactured from pure 100% polypropylene
- Spun fibers provide a gradient density from the outer surface to the inner core

- Excellent bacteria and chemical resistance
- High dirt-holding capacity and superior sediment filtration (as Tested by American Plumber®)



The W5P is Tested and Certified by NSF International under NSF/ANSI Standard 42 for material requirements only.

Model Number	Part Number	Medium	Rating (nominal)	Maximum Flow Rate	Diameter	Length
W5P	155014-52	Polypropylene	5 micron	10 gpm	2 ³ / ₈ "	9 ⁷ / ₈ "
W25P*	155015-52	Polypropylene	25 micron	10 gpm	2 ³ / ₈ "	9 ⁷ / ₈ "

* Not Performance Tested or Certified by NSF

Heavy-Duty Spun Polypropylene Depth



WDGD-5005

- Whole-House filter cartridge
- Manufactured from pure 100% polypropylene
- Excellent bacteria and chemical resistance

- Spun fibers provide a variable density from the outer surface to the inner core



Tested and Certified by NSF International.

Model Number	Part Number	Medium	Rating (nominal)	Maximum Flow Rate	Diameter	Length
WDGD-5005	155337-51	Polypropylene	5 micron*	10 gpm	4 ¹ / ₂ "	9 ⁷ / ₈ "

* As Tested by American Plumber

Thermally-Bonded Polypropylene



WPD-110
WPD-25

- Whole-House filter cartridges
- Manufactured from pure 100% polypropylene
- More efficient than resin-bonded cartridges

- Thermal-bonded microfiber construction
- Withstand high-pressure differentials



Tested and Certified by NSF International.

Model Number	Part Number	Medium	Rating (nominal)	Maximum Flow Rate	Diameter	Length
WPD-110	155750-52	Polypropylene	5 micron*	10 gpm	2 ¹ / ₂ "	9 ⁷ / ₈ "
WPD-25	155751-52	Polypropylene	25 micron*	10 gpm	2 ¹ / ₂ "	9 ⁷ / ₈ "

* As Tested by American Plumber