

FILTER housings

Heavy-Duty

- Large capacity housings for whole-house and high-flow applications
- Pressure relief button
- 1 or 1½-inch NPT inlet/outlet
- 10- and 20-inch lengths
- Clear or opaque sump
- Accepts large capacity 4½-inch diameter cartridge

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
W10-PR	152014	Gray	Black	1"	7¼" x 13⅝"	30-100 psi	40-100°F	WMB20, WWHD
W2010-PR	152015	Gray	Black	1"	7¼" x 23⅝"	30-100 psi	40-100°F	WMB20, SW-4
W15-PR	152016	Gray	Black	1½"	7¼" x 13⅝"	30-100 psi	40-100°F	WMB20, WWHD
W2015-PR	152017	Gray	Black	1½"	7¼" x 23⅝"	30-100 psi	40-100°F	WMB20, SW-4
W10-BC*	152080	Clear	Blue	1"	7¼" x 13⅝"	30-100 psi	40-100°F	WMB20, WWBC



- Whole-House filter housing
- Low-cost alternative to stainless and carbon steel housings
- Durable glass-reinforced nylon construction
- ¾-inch NPT inlet/outlet
- Install unit after hot-water heater to reduce suspended sediment

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
WH34	152009	Red	Red	¾"	5⅝" x 12⅝"	30-125 psi	30-160°F	WMB34, WW34



- Whole-House filter housings
- 304 stainless steel
- ¾-inch NPT inlet/outlet
- For use with hot-water or high-pressure applications
- Accept a wide variety of 2½ to 3-inch diameter cartridges

Model Number	Part Number	Sump Color	Cap Color	Inlet/Outlet	Overall Dimensions	Operating Pressure	Operating Temperature	Optional Accessories†
ST-1	156017-02	SS	SS	¾"	4⅞" x 12⅞"	250 psi	300°F	—
ST-2	156018-02	SS	SS	¾"	4⅞" x 22¾"	250 psi	300°F	—



*The W10-BC includes a unique spanner wrench and replacement o-ring.
†See page 14 for part number and description.
Note: See chart on page 16 for flow rates with specific cartridges.