

TASTE & ODOR cartridges

Carbon-Impregnated Cellulose



W5CIP
W.5CIP478

- Point-of-Use filter cartridges
- Economically priced
- Dual-purpose cartridges
- Design maximizes dirt-holding capacity

- Reduce bad taste & odor, chlorine taste & odor, and sediment (as tested by American Plumber®)
- Designed for municipal/chlorinated water (not recommended for well water)



COMPONENT

The W5CIP is Tested and Certified by NSF International for material requirements only.

Model Number	Part Number	Medium	Chlorine T & O Reduction @ Flow Rate	Maximum Flow Rate	Diameter	Length
W5CIP478*	155022-52	Carbon-impregnated Cellulose	>2500 gal @ 0.5 gpm*	1 gpm	2 7/8"	4 7/8"
W5CIP	155022-52	Carbon-impregnated Cellulose	>5000 gal @ 0.5 gpm*	5 gpm	2 7/8"	9 3/4"

Granular-Activated Carbon (GAC)



WCC
WGC478

- Point-of-Use filter cartridges
- Effective taste, odor, and chlorine taste & odor reduction
- Nominal 20-micron postfilter reduces carbon fines and suspended particles

- Cartridge design ensures that water passes through the entire length of the carbon bed, maximizing contact time

Model Number	Part Number	Medium	Chlorine T & O Reduction @ Flow Rate	Maximum Flow Rate	Diameter	Length
WGC478*	155110-51	Granular-Activated Carbon	>750 gal @ 0.5 gpm*	1 gpm	2 7/8"	4 7/8"
WCC*	155155-51	Granular-Activated Coconut Carbon	>500 gal @ 1 gpm*	1 gpm	2 7/8"	9 3/4"
WGCHD*	155153-51	Granular-Activated Carbon	>12500 gal @ 2 gpm*	2 gpm	4 1/2"	9 3/4"

Carbon Block



W5CB

WLC-R

- Point-of-Use filter cartridges
- Excellent bad taste, odor, and chlorine taste & odor reduction (as tested by American Plumber)
- Available in a wide range of sizes to fit both Standard and Heavy-duty filter housings

- Specialty blocks are capable of reducing cysts, lead and certain volatile organic chemicals (VOCs) (as tested by American Plumber)



COMPONENT

The W5CB and WLC-R are Tested and Certified by NSF International for material requirements only.

Model Number	Part Number	Medium	Reduces	Rating (nominal)	Chlorine T & O Reduction @ Flow Rate	Lead	VOCs	Dia.	Length
W5CB478*	155169-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>3000 gal @ 1 gpm*	N/A	N/A	2 7/8"	4 7/8"
W5CB	155162-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>20000 gal @ 1 gpm*	N/A	N/A	2 7/8"	9 3/4"
W5CBHD*	155170-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts*	0.5 micron	>5000 gal @ 4 gpm*	N/A	N/A	4 7/8"	9 3/4"
WLC-R	155268-51	Acid-washed Bituminous	Chlorine Taste & Odor, Cysts, Lead, VOCs*	0.5 micron	>20000 gal @ 0.6 gpm*	600*	300*	2 7/8"	9 3/4"

*As tested by American Plumber
Certain states require registration for health-related claims.