



A CSW Industrials Company

PRODUCT DATA SHEET

FALCON WATER CONNECTIONS

Potable Water Expansion Tanks

Description

Falcon Expansion tanks are designed to protect water heaters from damage caused by thermal expansion. This is a process where water expands as it heats up, creating extra pressure that can cause tanks to burst or leak. Installing a thermal expansion tank is a great way to increase the lifespan of your water heater and prevent costly repairs by helping regulate pressure within the water heater. The 16 gauge cold rolled steel tank used in the construction of these tanks is a robust solution that ensures longevity and durability. In addition, the 100% butyl diaphragm design delivers superior performance and ensures that the tank remains leak-free for the long run.

The factory pre-charge of 40 psi ensures that the thermal expansion tank is ready to use straight out of the box. It is important to note that the tank should not be used over 80 psi as this can shorten its lifespan. To ensure correct usage, homeowners must install a pressure reducing valve that will prevent excessive pressure from damaging the tank.



Application

- Absorb excess water created by thermal expansion
- Closed hot water heating systems

Recommended Use

- Water Heaters
- Tankless Water Heaters
- Boilers

Approvals

- WQA NSF 61/372
- UPC/IAPMO listed



Characteristics | Features

- 16 gauge cold rolled steel tank
- 100% butyl rubber diaphragm
- Stainless steel NPT Connection
- 100% pressure tested
- Brass air valve with o-ring seal

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
Thermal Expansion Tanks				
EXPTMINI	Mini expansion tank - 1/2" MIP SS Connection	1	1	0.046
EXPT2	Thermal expansion tank - 2.1 gallon - 3/4" MIP SS connection	1	5	0.48
EXPT4	Thermal expansion tank - 4.8 gallon - 3/4" MIP SS connection	1	9	1.05
EXPT10	Thermal expansion tank - 10.1 gallon - 3/4" MIP SS connection	1	16	1.96
EXPT14	Thermal expansion tank - 14.5 gallon - 1" FIP SS connection*	1	27	3.62

*Item is a floor mount expansion tank

WARNING - This product can expose you to chemicals including Carbon Disulfide, Nickel, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Limited Warranty



For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

PO Box 5266, Brendale, Qld 4500, Australia • 1300 772 878 • rectorseal.com.au

3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2025 RectorSeal. All rights reserved. R51047-0625