


PRODUCT SUBMITTAL 249

PRO-BALANCE® White Surface Mount Heating Manifold Cabinets



Product: PRO-BALANCE® White Surface Mount Heating Manifold Cabinets

Date: 10 July 2023 (supersedes 19 January 2018)



Article No.	Typical Station Configuration	Frame/Cabinet Opening		Outside Cabinet Dimensions		
		A in (cm)	B* in (cm)	W in (cm)	H in (cm)	D in (cm)
347400-512	up to 3	16 (43)	19 (49)	19.7 (50.0)	28.7 (73.0)	5.1 (13)
347410-512	up to 5	20 (53)	19 (49)	23.8 (60.5)	28.7 (73.0)	5.1 (13)
347420-512	up to 8	28 (73)	19 (49)	31.7 (80.5)	28.7 (73.0)	5.1 (13)
347430-512	up to 11	36 (93)	19 (49)	39.6 (101)	28.7 (73.0)	5.1 (13)
347440-512	up to 12	44 (113)	19 (49)	47.4 (121)	28.7 (73.0)	5.1 (13)
347450-512	up to 12	50 (128)	19 (49)	53.3 (135)	28.7 (73.0)	5.1 (13)

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.
© 2023 REHAU

PRODUCT SUBMITTAL 249

PRO-BALANCE® White Surface Mount Heating Manifold Cabinets



TECHNICAL DESCRIPTION

Material	20-gauge, galvanized steel with basic white powder coat finish (RAL 9016 / Pantone 705)
----------	---

FUNCTIONAL DESCRIPTION

PRO-BALANCE manifold cabinets for surface installation. The cabinets are made from 20-gauge galvanized steel with basic white powder coat finish (RAL 9016 / Pantone 705). Internal brackets allow for easy mounting of PRO-BALANCE 1 and 1 1/4 in. brass manifolds. Cabinet steel door comes with white slotted cabinet lock(s). Accessory item sold separately is the keyed cabinet lock (Art. 217688-001) which replaces an existing slotted cabinet lock.

Installation Note: manifold cabinet should be installed before manifold, screed and thermal mass

*Removable cover-plate below door temporarily extends cabinet opening to the floor (27 in / 69 cm).



Cover-plate and door removed



Door removed



Fully assembled cabinet

For updates to this publication, visit na.rehau.com/resourcecenter

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained therefrom. Before using, the user will determine suitability of the information for user's intended use and shall assume all risk and liability in connection therewith.

© 2023 REHAU