

resideo



SAFETY AND COMFORT MADE EASY

Get peace of mind from the added safety a mixing valve provides



Resideo Braukmann AM-1 Series Thermostatic Mixing Valve

Designed for point-of-use applications.

COLOR-CODED

New black lockable handwheel prevents tampering and is required by the new ASSE 1070 standard.

EASY INSTALLATION

Available in multiple connection types, including new ProPress fittings, Union Push Connect, PEX, NPT, Sweat, and CPVC.

MEETS LEAD-FREE CODES

All of our AM-1 1070 mixing valves are now available in Low-Lead-Content version.

ASSE 1070 & 1017 APPROVED


For point-of-use requirements.

HIGH CV RATING

Of 1.8.

TEFLON® COATING

Resists mineral deposit build-up and extends service life.



FREE THERMOSTRIP® INCLUDED

Makes temperature setting
easy for one person to handle.

MODEL NUMBER	SIZE	CONNECTION TYPE	TEMPERATURE
AM100C1070-UP-1LF	1/2"	Union ProPress	70° –120° F (21° –49° C)
AM100C1070-UCPVC-1LF	1/2"	Union CPVC	
AM100C1070-UPEX-1LF	1/2"	Union PEX	
AM100C1070-US-1LF	1/2"	Union Sweat	
AM100C1070-UT-1LF	1/2"	Union NPT	
AM100C1070-SB-1LF	1/2"	Union Push Connect	
AM100C1070-USTG-LF	1/2"	Union Sweat w/ Temp Gauge	
AM101C1070-UP-1LF	3/4"	Union ProPress	
AM101C1070-SB-1LF	3/4"	Union Push Connect	
AM101C1070-UCPVC-1LF	3/4"	Union CPVC	
AM101C1070-UPEX-1LF	3/4"	Union PEX	
AM101C1070-US-1LF	3/4"	Union Sweat	
AM101C1070-UT-1LF	3/4"	Union NPT	
AM101C1070-USTG-LF	3/4"	Union Sweat w/ Temp Gauge	
AM102C1070-US-1LF	1"	Union Sweat	
AM102C1070-UT-1LF	1"	Union NPT	
AM102C1070-SB-1LF	1"	Union Push Connect	
AM102C1070-UP-1LF	1"	Union ProPress	
AM102C1070-USTG-LF	1"	Union Sweat w/ Temp Gauge	



Resideo Technologies, Inc.

1985 Douglas Drive North
Golden Valley, MN 55422
1-800-468-1502
resideo.com

For more information

resideo.com/pro/water