

Job Name _____
 Purchaser _____
 Submitted to _____
 Unit Designation _____

Location _____
 Engineer _____
 Reference ☐ Approval ☐ Construction ☐
 Schedule # _____

Specifications

Model	Indoor Unit Model Number (US Code)		AC042NN4DCH/AA (CNH424DN)
	Outdoor Unit Model Number (US Code)		AC042JXADCH/AA (CXH42ADJ)
Performance	Nominal Capacity	Cooling / Heating (Btu/h)	42,000 / 47,000
	Capacity Range	Cooling (Btu/h)	16,300 - 45,000
		Heating (Btu/h)	13,400 - 50,000
	SEER / EER		19.60 / 10.40
	COP (nominal heating)		3.16
	HSPF		9.50
AHRI Certification Number		202087969	
Power	Voltage	ø / V / Hz	1 / 208-230 / 60
	Working Voltage Range (VAC)		176 - 254 (max. 3% deviation from each)
	Operating Current (min. / std. / max.)	Cooling (A)	5.6 / 18.7 / 21.0
		Heating (A)	4.3 / 20.10 / 25.0
	Max. Breaker	Amps	35
	Min. Circuit Ampacity (A)	22.08	
Dimensions	W X H X D (in.)	Indoor Unit	33 1/16 X 11 3/8 X 33 1/16
		Outdoor Unit	37 X 48 X 13
	Weight (lbs.)	Indoor Unit	40.79
		Outdoor Unit	194
Heat Exchanger	Indoor Unit	Type	Aluminum Fin / Copper Tube
		FPI	18
		Pipe Diameter (in.)	1/4
	Outdoor Unit	Type	Aluminum, flat fin, micro channel
Sound Pressure Level	Indoor Unit dB(A)	L / M / H	34 / 40 / 44
	Outdoor Unit dB(A)	Cooling / Heating (high)	51 / 53
Operating Temperatures °F(°C)	Outdoor	Cooling	23 ~ 115°F (-5 ~ 46°C)
		Heating	0 ~ 115°F (-18 ~ 46°C) w/ baffle
	Indoor	Cooling	-4 ~ 75°F (-20 ~ 24°C)
		Heating	61 ~ 90°F (16 ~ 32°C) T ≤ 80°F (27°C)
Pipe Connections	Indoor & Outdoor	High side (flare)	3/8"
		Low side (flare)	5/8"
	Maximum (ft.)		246
	Maximum Vertical Separation (ft.)		98
Condensate Connection		1 1/4" OD, 1" ID	
Refrigerant	Type		R410A
	Control Method		Electronic Expansion Valve
	Factory Charge	oz.	98.77
	Charged for	25 ft	
Additional Refrigerant		0.355 oz/ft over 25 ft	
Compressor	Manufacturer		Samsung
	Type		Inverter Driven, Twin BLDC, Rotary
	RLA	A	17.0
Evaporator Fan	Type		BLDC With Turbo Type Fan (1)
	Air Volume	CFM (L/M/H)	670/ 890 / 1170
	Output	Watts	93
	Operating Current	Amps	0.35
Condenser Fan	Motor		BLDC With Axial Type Fan (2)
	FLA / Watts / CFM (max.)		0.48 A X 2 / 125 W X 2 / 3,040 CFM
Fascia Panels	Model Number		PC4NUFMUN (WindFree™)
	L X W X H (in.)		37 3/8 X 37 3/8 X 2 1/2
	Weight (lbs.)		13.89
Safety	Certifications		
	Devices	ETL (UL 1995) PCB fuses, indoor unit terminal block thermal fuse, current transformer, over-voltage protection, crankcase heating, temperature limit protection logic, compressor overload sensing	

Certified in accordance with the AHRI Unitary Small Air-Source Heat Pumps (USHP) Certification Program which is based on the latest edition of AHRI Standard 210/240.

*The WindFree™ unit delivers an air current that is under 0.15 m/s while in WindFree™ mode. Air velocity that is below 0.15 m/s is considered "still air" as defined by ASHRAE (American Society of Heating, Refrigerating, and Air-Conditioning Engineers).

Warranty

10 years compressor, 10 years parts, 1 year limited labor (conditions apply)



- The outdoor unit shall supply power to indoor unit via 14 AWG X 3 power wire
- Auto-restart after power loss
- The outdoor unit shall have a snow accumulation prevention option setting to prevent snow drifting against an idle outdoor unit.
- The indoor unit shall have a removable EEPROM that stores system programming information, unit name, and other data
- Electro-static, washable, pleated filter as standard (included with fascia panel).
- Knock-out for outside air capability (with booster fan connection)
- Fascia panel shall have LED indicator lights, IR receiver, and 4 motorized louvers (independent louver control is possible with wireless or premium wired controller).
- The outdoor unit shall have a night time quiet mode option to reduce operating sound during the night.
- Built in condensate pump with maximum 29" lift from the bottom of the unit, check valve, and float switch that disables indoor unit during overflow detection
- WindFree™ function will close the supply air outlet louver while in cooling mode to gently disperse cool air into the space without blowing directly onto occupants. The WindFree™ feature is optional and can be enabled using central or local control options (MWR-SH11UN, MWR-WG00UN, AR-EH03U only).
- The WindFree™ panel (PC4NUFMUN) has an integral humidity sensor that will open the louvers for standard cool mode when space conditions could potentially cause condensation formation on the panel surface.
- The WindFree™ 4-way cassette can be configured for 2-stage operation, cooling the space with the louver open (fixed or swing) until the room temperature nears set temperature. Once room temperature is near set temperature, WindFree™ operation will start automatically, closing the louver and using the face of the fascia panel to gently cool the space with still air*.
- Pipe connections at the outdoor unit shall be made inside the unit chassis. Refrigerant pipes can exit through the front, side, rear, or bottom sides of the outdoor unit.

Construction

The outdoor unit shall be galvanized steel with a baked on powder coated finish for durability

The indoor unit shall have a galvanized steel frame with HIPS chassis and fascia panel certified to UL94 V0.

Heat Exchanger

The indoor unit heat exchanger shall be mechanically bonded fin to copper tube

The outdoor unit heat exchanger shall be aluminum, flat fin, micro channel

Controls

Control signal shall be a DDC type signal

Interconnect control wire between outdoor and indoor unit shall be 16 AWG X 2 shielded
 Wired or wireless controllers must be purchased separately

The system shall integrate with the Samsung NASA Controls Solution

Refrigerant System

The refrigerant shall be R410A

The compressor shall be hermetically sealed, inverter controlled, twin BLDC Rotary

Refrigerant flow shall be controlled by an electronic expansion valve at outdoor unit

Soft-start to reduce current demand during compressor start


Required Accessories

Fascia Panel	WindFree™	☐ PC4NUFMUN
--------------	-----------	------------------------------------


*A fascia panel is required for cassette unit operation and is sold separately.

Optional Accessories

Wired Controller	Simplified Touch Controller	☐ MWR-SH11UN
	Advanced Wired Controller	☐ MWR-WG00UN
Wi-Fi Adapter		☐ MIM-H04UN
External Temperature Sensor		☐ MRW-TA
Wireless Controller		☐ AR-EH03U
External Contact Control		☐ MIM-B14
Wall Bracket (for outdoor unit)		☐ CKN-250
Wind Baffles	Front	☐ WBF-1M2
	Back	☐ WBB-2M-B
Line Sets - insulated and flared, interconnect cables included		☐ 25' - ILS-2510
		☐ 50' - ILS-5010
Thermostat Adaptor (for connection to a standard 24VAC thermostat)		☐ MIM-A60UN
Motion Detection Sensor		☐ MCR-SMC







Sub-duct connection cannot be applied if WindFree™* mode will be used.



Proper clearance must be maintained around unit for proper operation.

No.	Name	Description
①	Liquid Pipe Connection	Ø 3/8" Flare
②	Gas Pipe Connection	Ø 5/8" Flare
③	Drain Pipe Connection	OD 1 1/4", ID 1"
④	Conduit for Power & Communication Wiring	-
⑤	Air Inlet Grille	-
⑥	Air Outlet Louver	-
⑦	Fresh Air Inlet	Ø 4"

Samsung WindFree™ 4-Way Cassette, Single Zone, Split
System AC042JXADCH/AA (CXH42ADJ) Dimensional Drawing



No.	Description
1	Suction service valve
2	Liquid service valve
3	Power and communication conduit openings