



6032MTCD



When ordering, please specify tile flange locations.

60" x 32" x 3" (exterior bottom of base)	
MULTIPLE, LOW-PROFILE THRESHOLD smooth floor	
Center Drain	
Acrylic CXL®	DoloMatte®
100 lbs / 45 kg	113 lbs / 51 kg



Model #	Material	Color / Finish	MSRP
SB6032MTCD	Acrylic CXL®	White (CWH) or Biscuit (CBS) / Gloss	\$1,880
SBDM6032MTCD	DoloMatte®	White (CWH) / Matte	\$2,250

Must specify color code on order. DoloMatte available in white only. Not for use in steam shower applications.

Options <i>Must be ordered at time of purchase</i>
Quick Ship (QSPRI) \$450 Reduces lead time. Please call for availability.
Radiance® (RAD100) \$1,675 Shower floor heating system. Radiance heating grids are fully integrated within the acrylic shell structure of the shower floor. Requires a 110-volt, 15 amp GFCI and remote installation of control box & keypad.
Pre-Leveled Foam Base (PLFSB) \$230
PVC Drain Kit Finishes Chrome included with shower base Brushed Nickel upcharge (SBSQDBN) \$130



Factory-installed tile flange is 1/16" thick.
Account for this thickness when planning final opening size.

Accessories
Drain Kit Solid Brass Drain Kit with Stainless Steel Trim (SBSQDSB) \$205
Teak Shower Seat Premium Natural Stainless (TK-SSEAT2416BNS) \$3,125 High-Polished Stainless (TK-SSEAT2416BHP) \$3,570 Standard Natural Stainless (TK-SSEAT2215NS) \$1,160 High-Polished Stainless (TK-SSEAT2215HP) \$1,620
Teak Bath Mat (TKMAT3018) \$840 Measures 30" x 17.5" x 1" Custom sizes also available. Contact MTI for details.
Teak Shower Tray (TK6032MTCD) Contact MTI for pricing

IMPORTANT ORDERING & INSTALLATION INFORMATION

- Factory-installed tile flange on 1, 2 or 3 sides to facilitate installation. Must specify tile flange location(s) on order.
- 3.5" drain opening pre-drilled.
- Dimensions provided represent the length and width of the bottom of the base without tile flange. See Installation Instructions.
- Add proper wet-bedding compound to fully support bottom of shower base. Optional factory installed Pre-Leveled Foam Base negates the need to wet bed when installing on a flat, level subfloor. See installation instructions.
- All bases are in accordance with CSA B45.5/IAPMO Z124 standard and compliant with ASTM C 1028-07 coefficient of friction. DoloMatte bases meet ANSI A137.1/A326.3 coefficient of friction and AS HB198:2014 pendulum slip resistance testing.

- Options and accessories may be packaged inside the box. Always check packaging before discarding.
- All product measurements are ±1/2".
- Specifications and configurations are subject to change without notice.
- Measurements herein supersede all others published prior to publication date below.

See the Installation & Operation Manual for more details.

MTI's Customer Service: Monday-Friday 8am-6pm EST

800-783-8827 or service@mtibaths.com

CSA # MTSB-6032MTCD

HURL # MTSB-DM6032MTCD

©2024 by MTI Baths, Inc. Modification Rights Reserved



Rev. 04 30 2024