

CODE NUMBER

2172229

DESCRIPTION

Vitreous China Floor-Mounted Rear Outlet Water Closet with SloanTec® Glaze.

DETAILS

- Flush Volume: 1.28–1.6 gpf (4.8–6.0 Lpf)
- Flush volume determined by the flushometer used with the fixture
- Rim Height: 16 ½" (419mm)
- Nominal Dimensions: 26 ¾" × 14" × 16 ½" (679 × 356 × 419mm)

FEATURES

- White Vitreous China
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Permanent SloanTec® hydrophobic antimicrobial glaze inhibits the growth and buildup of germs, bacteria, mold, mildew and mineral scale on the surfaces
- Elongated bowl
- Floor mounted, rear outlet
- Water spot area: 10¼" x 8" (26 cm x 24 cm)
- 1½" I.P.S. top spud inlet
- 2⅝" fully glazed trapway
- Syphonjet flushing achieves up to 1000g Map Scores when used with Sloan flushometers
- Closet bolts and caps included
- Toilet seat not included

RECOMMENDED SEATS

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Church - 295CT/295SSCT & 2155CT/2155SSCT

PLUMBING SYSTEM REQUIREMENTS


- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)

DOWNLOADS

- [HET ST-2229 Series Installation Instructions](#)
- [SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide](#)
- [Additional Downloads](#)



COMPLIANCES & CERTIFICATIONS



(ADA Compliant, BAA Compliant, CalGreen Compliant, CEC Compliant, cUPC Green Certified, cUPC Certified, EPD, HPD, WaterSense Listed, Satisfies LEED Credits, WELL Building Standard)

NOTES

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

[Find a compatible flushometer](#) for this water closet.

WaterSense compliant when used with a WaterSense compliant flushometer

WARRANTY

[View Warranty Information](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Technical drawing of the Bed Pan Model 1000, showing front and side views with dimensions in inches and millimeters.

Front View Dimensions:

- Overall width: $18\frac{1}{2}$ [470]
- Top mounting hole offset: $1\frac{1}{8}$ [29]
- Top mounting hole diameter: $5\frac{1}{2}$ [140]
- Top mounting hole center-to-center distance: $8\frac{3}{4}$ [223]
- Label: "Bed pan models only"

Side View Dimensions:

- Overall height: $29\frac{5}{8}$ [752]
- Height to top of seat: $26\frac{7}{8}$ [683]
- Seat height: $5\frac{3}{8}$ [135]
- Seat width: $8\frac{1}{2}$ [215]
- Seat thickness: 4 [102]
- Base width: $13\frac{1}{2}$ [343]
- Overall base width: $25\frac{3}{8}$ [645]

Technical drawing of the front view of a chair. The drawing includes the following dimensions:

- Top width: 15 [381]
- Seat height: 16-1/2 [419]
- Backrest height: 4 [102]
- Seat width: 6 [152]
- Base width: 9-5/8 [244]

Page 2 of 2