

Series 63

PVC Compression Tee

- Max 150 psi @ 73°F
- Certified to NSF/ANSI 14 / Annex G Lead Free



Size IN	Part Number	Packing	Weight LB
	Comp x Comp x FIP		
1/2	02946300	56	0.3
3/4	02946312	42	0.4
1	02946314	30	0.6
1-1/4	02946316	18	0.8
1-1/2	02946318	14	1.0
2	02946320	18	1.3
3/4 x 1/2	02946390	42	0.4

Series 63

PVC Slip Compression Tee

- Max 150 psi @ 73°F
- Iron pipe sizes
- Certified to NSF/ANSI 14 / Annex G Lead Free



Size IN	Part Number	Packing	Weight LB
	Comp x Comp x Slip		
1/2	02946350	56	0.2
3/4	02946362	42	0.2
1	02946364	30	0.3
1-1/4	02946366	18	0.4
1-1/2	02946368	14	0.6
2	02946370	18	0.8

Series 62

PVC Compression Coupling

- Max 150 psi @ 73°F
- Iron pipe sizes
- Certified to NSF/ANSI 14 / Annex G Lead Free



Size IN	Part Number	Packing	Weight LB
	Comp x Comp		
1/2	02946200	56	0.3
3/4	02946212	48	0.4
1	02946214	32	0.5
1-1/4	02946216	20	0.8
1-1/2	02946218	16	0.9
2	02946220	18	1.3
2-1/2	02946225	6	2.3
3	02946230	8	3.7
4	02946240	3	5.3

Series 82

Galvanized Compression Coupling

- Max. 125 psi @ 210°F
- Seamless body and nut
- Zinc plated surface finish
- Long pattern



Size IN	Part Number Comp x Comp	Packing		Weight LB
		Inner	Master	
1/2	02948200	12	72	1.0
3/4	02948212	12	72	1.2
1	02948214	12	48	1.6
1-1/4	02948216	6	36	2.0
1-1/2	02948218	6	24	2.4
2	02948220	6	18	3.6

Series 92

Brass Compression Coupling

- Max. 125 psi @ 210°F
- Brass body
- Long pattern



Size IN	Part Number Comp x Comp	Packing		Weight LB
		Inner	Master	
3/8	02949200	24	96	0.5
1/2	02949212	12	120	0.6
3/4	02949214	12	48	1.1
1	02949216	12	36	1.2
1-1/4	02949218	12	36	1.6
1-1/2	02949220	12	24	1.9
2	02949222	12	24	2.8

Series 32

CPVC Compression Coupling

- Max. 100 psi @ 180°F
- Copper tube sizes
- Certified to NSF/ANSI 14 / Annex G Lead Free



Size IN	Part Number Comp x Comp	Packing	Weight LB
1/2	02943200G	125	0.2
3/4	02943200I	56	0.3