

F	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION 				
	HOSE VALVES									
5670	BENT NOSE WITH FLANGE					 ☐ Fig. 5670 (Less Vacuum Breaker) ☐ Fig. 5670 -H (With Vacuum Breaker) NOTES: - The AB100, AB1953, California Lead Law, and NSF/ANSI Standard 61 - Drinking Water Components are not applicable to Jay R. Smith hydrants as they do not convey/dispense water for human consumption through drinking or cooking. - Dimensions shown in parentheses are in millimeters. FOR IRRIGATION PURPOSES ONLY. REGULARLY FURNISHED: Hose Valves have a Rough Finish Brass Body with Machined Brass Vandal-Resistant Lock Shield Bonnet, Removable Wheel Handle, 3/4"(19) NPT Female Threaded Inlet and 3/4"(19) Hose Connection. OPTIONAL MATERIALS: ☐ Polished Chrome Plated -CP ☐ Rough Chrome Plated -CR Installer is responsible for providing a 100% watertight positive seal at the hydrant to wall interface. Seal all the flange with an appropriate sealant recommended by a sealant manufacturer. NOTE: Jay R. Smith does not warrant the performance or life expectancy of the sealant material.				
	$3\frac{1}{2}"(89)$ $2\frac{1}{4}"(57)$ $2"(51)$ $2\frac{3}{4}"(70)$									
5670										
DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE										
FIGURE NUMBER 	REV. 	DATE 	DESCRIPTION 	BY 	CKD. BY 	WEIGHT POUNDS 	VOLUME CUBIC FEET 	FIGURE NUMBER 5670		



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov