



All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Short Socket Tees

Socket Style Sch 40

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	16.47
S401-251	2x2x1-1/2	25	0	015	16.47



Male Thread Tee (Branch)

Socket x Socket x Mipt

402B-010	1	50	0	040	7.20
----------	---	----	---	-----	------



Spigot Tee, 2"

Spigot x Spigot x Spigot Sch 40

404A-020	2	30	0	015	17.18
----------	---	----	---	-----	-------



90° Ell, 2"x1-1/2" Reducing, Socket/Spigot

2"x2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	20.68
----------	---------	----	---	-----	-------



90° Ell 2-1/2"x2" Reducing Socket/Spigot

2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	24.22
----------	------------------------	----	---	-----	-------



90° Spigot Ell, 1-1/2"

Spigot x Spigot Sch 40

422-015	1-1/2	25	0	015	16.59
---------	-------	----	---	-----	-------



45° Street Ell -Short Spigot

Spigot x Socket Sch 40

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	14.66
----------	---	----	---	-----	-------



45° Street Ell

Spigot x Socket

427-005	1/2	50	400	040	2.22
427-007	3/4	50	0	040	3.46
427-010	1	50	0	040	4.12
427-012	1-1/4	25	0	040	5.77
427-015	1-1/2	25	0	040	7.20
427-020	2	25	0	040	9.43
427-025	2-1/2	10	0	040	30.69
427-030	3	10	0	040	38.10
427-040	4	5	0	040	68.30
427-050	5	4	0	040	205.33
427-060	6	4	0	040	210.93
427-080	8	2	0	040	507.33
427-100	10	1	0	041	1334.92
427-120	12	1	0	041	1957.11
427-140F	14	1	0	047	1458.59
427-160F	16	1	0	047	1982.53
427-180F	18	1	0	047	2164.12
427-200F	20	1	0	047	2746.91
427-240F	24	1	0	047	4326.93



22-1/2° Street Ell

Spigot x Socket

442-005	1/2	50	400	040	3.14
442-007	3/4	50	0	040	4.89
442-010	1	50	0	040	5.87
442-012	1-1/4	20	0	040	8.21
442-015	1-1/2	25	0	040	10.32
442-020	2	20	0	040	13.51
442-025F	2-1/2	1	18	047	76.31
442-030	3	5	0	040	78.72
442-040	4	4	0	040	121.52
442-060	6	4	0	040	299.99
442-060F	6	1	5	047	177.02
442-080	8	1	4	040	721.57
442-080F	8	1	4	047	266.66





Schedule 40 Fittings Product

Pool & Spa Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

22-1/2° Street Ell (continued)

Spigot x Socket

442-100F	10	1	0	047	412.63
442-120F	12	1	0	047	619.40

Grated Coupling, 2" Sch 40

Socket Style Sch 40

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	9.04
-----------	---	----	---	-----	------

Smooth Barb Adapter

Spigot x Smooth Barb

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015	3.88
432-007775	3/4	50	600	015	6.19
432-010775N	1(3/4)X3/4	50	400	015	6.48

"N" suffix indicates Nesting - Spigot also serves as size smaller socket

Venturied Tee, Multi Configuration - Socket Style Sch 40

1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	16.33
473-210-1/4	with 1/4" Nozzle	25	0	015	16.33
473-210-3/8	with 3/8" Nozzle	25	0	015	16.33

Venturied Tee, Multi Configuration - Socket Style Sch 40

1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	13.32
473-825-3/8	with 3/8" Nozzle	50	0	015	13.32
473-825-1/4	with 1/4" Nozzle	50	0	015	13.32

Venturied Tee, Multi Configuration - Socket Style Sch 40

Individual Nozzles Only

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	4.30
473-2	1/4" Nozzle	100	600	015	4.30

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Venturied Tee, Multi Configuration - Socket Style Sch 40

(continued)

Individual Nozzles Only

473-3	3/8" Nozzle	100	600	015	4.30
-------	-------------	-----	-----	-----	------

120° Wye, 1-1/2"x1"x1"

Spigot x Socket x Socket Sch 40

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	23.26
------------	-----------	----	---	-----	-------

120° Wye, 2"

Socket

475-020120	2	10	0	015	27.27
------------	---	----	---	-----	-------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	129.51
-----------	-------------	---	---	-----	--------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	152.43
-----------	-------------	---	---	-----	--------