



Schedule 40 Fittings Product PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
448-012	1-1/4	25	100	040	5.27
448-015	1-1/2	25	100	040	5.51
448-020	2	10	120	040	9.78
448-025	2-1/2	10	0	040	14.39
448-030	3	10	0	040	18.82
448-040	4	6	0	040	33.04
448-050	5	5	0	040	64.01
448-060	6	8	0	040	78.09
448-080F	8	1	2	047	381.13
448-100F	10	1	2	047	774.47
448-120F	12	1	4	047	1547.48

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	14.06
-----------	-------	----	-----	-----	-------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	3.63
449-005	1/2	50	1000	040	2.94
449-007	3/4	50	300	040	3.46
449-010	1	50	200	040	4.12
449-012	1-1/4	25	150	040	5.51
449-015	1-1/2	25	100	040	7.06
449-020	2	10	120	040	8.70
449-025	2-1/2	10	0	040	14.93
449-030	3	10	0	040	19.67
449-040	4	6	0	040	44.52
449-060	6	6	0	040	60.27
449-060F ⁴	6	1	6	047	152.54
449-080F ⁴	8	1	6	047	234.86
449-100F ⁴	10	1	0	047	539.16
449-120F ⁴	12	1	0	047	881.56
449-140F ⁴	14	1	2	047	966.44
449-160F ⁴	16	1	0	047	1068.77
449-180F ⁴	18	1	0	047	1907.23
449-200F ⁴	20	1	0	047	3489.16
449-240F ⁴	24	1	0	047	4644.58

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	3.46
449-010CS	1	50	300	040	4.12

Plug

Mipt

450-003	3/8	50	700	040	3.96
450-005	1/2	50	300	040	3.63
450-007	3/4	50	300	040	3.89
450-010	1	50	300	040	6.37
450-012	1-1/4	25	300	040	6.71
450-015	1-1/2	25	150	040	7.18
450-020	2	10	120	040	9.28
450-025	2-1/2	10	80	040	12.90
450-030	3	10	0	040	19.49
450-040	4	6	0	040	44.02
450-060	6	6	0	040	129.08
450-080	8	6	0	040	157.73
450-080F ⁴	8	1	4	047	342.22
450-100F ⁴	10	1	3	047	681.99
450-120F ⁴	12	1	0	047	952.10

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
 2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	5.77
475-007	3/4	20	0	040	9.04
475-010	1	25	0	040	12.67
475-012	1-1/4	20	0	040	19.46
475-015	1-1/2	20	0	040	24.98
475-020	2	10	0	040	74.93
475-025	2-1/2	8	0	040	171.26
475-030	3	5	0	040	126.22
475-040	4	4	0	040	238.04
475-050F ²	5	1	3	047	929.01
475-060	6	3	0	040	503.66
475-080	8	1	0	040	810.12
475-100	10	1	0	041	2684.37
475-100F ²	10	1	0	047	2252.48

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

475-120	12	1	0	041	3966.26
475-120F ²	12	1	0	047	3062.04
475-140F ²	14	1	0	047	4338.14
475-160F ²	16	1	0	047	5607.54
475-180F ²	18	1	0	047	7179.66
475-200F ²	20	1	0	047	8063.93
475-240F ²	24	1	0	047	10556.78

¹ Sized with Bushing

² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
 2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040	17.82
475-130 ¹	1X1/2	20	0	040	22.68
475-131 ¹	1X3/4	20	0	040	22.68
475-166 ¹	1-1/4X1/2	20	0	040	30.52
475-167 ¹	1-1/4X3/4	20	0	040	30.52
475-168 ¹	1-1/4X1	20	0	040	30.52
475-209 ¹	1-1/2X1/2	20	0	040	36.33
475-210 ¹	1-1/2X3/4	20	0	040	36.33
475-211 ¹	1-1/2X1	20	0	040	36.33
475-212 ¹	1-1/2X1-1/4	20	0	040	36.33
475-247 ¹	2X1/2	10	0	040	82.57
475-248 ¹	2X3/4	10	0	040	82.57
475-249 ¹	2X1	10	0	040	82.57
475-250 ¹	2X1-1/4	10	0	040	82.57
475-251 ¹	2X1-1/2	10	0	040	82.57
475-292 ¹	2-1/2X2	4	0	040	183.94
475-334 ¹	3X3/4	6	0	040	143.34
475-335 ¹	3X1	5	0	040	143.34
475-336 ¹	3X1-1/4	5	0	040	143.34
475-337 ¹	3X1-1/2	5	0	040	143.34
475-338 ¹	3X2	5	0	040	143.34
475-339 ¹	3X2-1/2	5	0	040	143.34
475-420	4X2	4	0	040	275.39
475-421 ¹	4X2-1/2	4	0	040	275.39
475-422 ¹	4X3	4	0	040	275.39
475-488F ²	5X3	1	4	047	738.91
475-490F ²	5X4	1	4	047	769.41
475-528 ¹	6X2	4	0	040	594.38
475-529 ¹	6X2-1/2	5	0	040	594.38
475-530 ¹	6X3	5	0	040	594.38
475-532	6X4	5	0	040	647.56
475-578F ²	8X2	1	2	047	1112.16

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047	1180.18
475-580F ²	8X3	1	2	047	1208.36
475-582	8X4	2	0	040	1109.26
475-582F ²	8X4	1	2	047	1246.36
475-585F ²	8X6	1	0	047	1284.18
475-621F ²	10X2	1	0	047	1336.90
475-622F ²	10X2-1/2	1	0	047	1359.87
475-623F ²	10X3	1	0	047	1432.52
475-624F ²	10X4	1	0	047	1515.91
475-626	10X6	1	0	041	2300.41
475-626F ²	10X6	1	0	047	1673.84
475-628	10X8	1	0	041	2556.04
475-628F ²	10X8	1	0	047	1791.01
475-661F ²	12X2	1	0	047	1814.71
475-663F ²	12X3	1	0	047	1858.01
475-664F ²	12X4	1	0	047	1944.52
475-666F ²	12X6	1	0	047	1953.89
475-668F ²	12X8	1	0	047	2265.90
475-670F ²	12X10	1	0	047	2590.78
475-691F ²	14X2	1	0	047	2157.26
475-693F ²	14X3	1	0	047	2334.92
475-694F ²	14X4	1	0	047	2448.69
475-696F ²	14X6	1	0	047	2758.83
475-698F ²	14X8	1	0	047	3161.17
475-700F ²	14X10	1	0	047	3531.18
475-702F ²	14X12	1	0	047	3956.29
475-751F ²	16X2	1	0	047	2506.38
475-753F ²	16X3	1	0	047	2709.43
475-754F ²	16X4	1	0	047	2817.64
475-756F ²	16X6	1	0	047	3170.78
475-758F ²	16X8	1	0	047	3610.94
475-760F ²	16X10	1	0	047	4018.90
475-762F ²	16X12	1	0	047	4478.50
475-764F ²	16X14	1	0	047	5069.04
475-781F ²	18X2	1	0	047	2734.70
475-783F ²	18X3	1	0	047	2859.86
475-784F ²	18X4	1	0	047	2902.36
475-786F ²	18X6	1	0	047	5560.69
475-788F ²	18X8	1	0	047	4150.07
475-790F ²	18X10	1	0	047	4616.07
475-792F ²	18X12	1	0	047	5355.10
475-794F ²	18X14	1	0	047	5879.59
475-796F ²	18X16	1	0	047	6166.30
475-811F ²	20X2	1	0	047	2875.59
475-813F ²	20X3	1	0	047	3116.17
475-814F ²	20X4	1	0	047	3156.54
475-816F ²	20X6	1	0	047	3215.77
475-818F ²	20X8	1	0	047	4346.96
475-820F ²	20X10	1	0	047	4832.52
475-822F ²	20X12	1	0	047	5823.91
475-824F ²	20X14	1	0	047	6517.70
475-826F ²	20X16	1	0	047	7224.19
475-828F ²	20X18	1	0	047	7754.56
475-901F ²	24X2	1	0	047	3629.80



Schedule 40 Fittings Product PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-903F ²	24X3	1	0	047	3709.67
475-904F ²	24X4	1	0	047	3811.90
475-906F ²	24X6	1	0	047	6709.37
475-908F ²	24X8	1	0	047	7318.88
475-910F ²	24X10	1	0	047	7396.17
475-912F ²	24X12	1	0	047	7829.11
475-914F ²	24X14	1	0	047	8097.72
475-916F ²	24X16	1	0	047	8480.29
475-918F ²	24X18	1	0	047	9219.09
475-920F ²	24X20	1	0	047	10077.23

¹ Sized with Bushing

² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	581.83
476-030F ²	3	1	3	047	958.32
476-040F ²	4	1	2	047	1067.52
476-060F ²	6	1	0	047	1215.68
476-080F ²	8	1	0	047	1480.51
476-100F ²	10	1	0	047	2714.83
476-120F ²	12	1	0	047	3232.04
476-140F ²	14	1	0	047	4703.92

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	210.40
476-420F ²	4X2	1	4	047	945.04
476-421F ²	4X2-1/2	1	2	047	986.01
476-422F ²	4X3	1	3	047	1014.39
476-528F ²	6X2	1	2	047	951.69
476-529F ²	6X2-1/2	1	2	047	1036.03
476-530F ²	6X3	1	2	047	1076.78
476-532F ²	6X4	1	0	047	1093.59
476-578F ²	8X2	1	2	047	1160.99
476-579F ²	8X2-1/2	1	0	047	1207.14
476-580F ²	8X3	1	0	047	1299.02
476-582F ²	8X4	1	0	047	1315.76
476-585F ²	8X6	1	0	047	1379.37
476-621F ²	10X2	1	0	047	1729.76
476-622F ²	10X2-1/2	1	0	047	1832.67

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	1885.20
476-624F ²	10X4	1	0	047	2071.40
476-626F ²	10X6	1	0	047	2323.47
476-628F ²	10X8	1	0	047	2422.92
476-661F ²	12X2	1	0	047	2467.84
476-662F ²	12X2 1/2	1	0	047	2495.84
476-663F ²	12X3	1	0	047	2629.80
476-664F ²	12X4	1	0	047	2681.14
476-666F ²	12X6	1	0	047	2833.29
476-668F ²	12X8	1	0	047	2905.97
476-670F ²	12X10	1	0	047	3078.59
476-756F ²	16X6	1	0	047	5172.94
476-786F ²	18X6	1	0	047	2898.00

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions



Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	13.19
457-007	3/4	15	90	040	14.98
457-010	1	10	60	040	15.43
457-012	1-1/4	5	30	040	49.76
457-015	1-1/2	5	20	040	51.80
457-020	2	5	0	040	69.88
457-025	2-1/2	5	0	040	97.80
457-030	3	5	0	040	156.26
457-040	4	4	0	040	216.36
457-060	6	1	0	040	480.76

Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	14.50
497-007	3/4	15	90	040	16.59
497-010	1	10	60	040	16.96
497-012	1-1/4	5	30	040	54.71
497-015	1-1/2	5	20	040	57.03
497-020	2	5	0	040	76.90
497-025	2-1/2	5	0	040	107.63
497-030	3	5	0	040	171.69
497-040	4	4	0	040	231.00
497-060	6	1	0	040	513.32

