



Schedule 40 Fittings Product

PVC Schedule 40 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
Cap (continued)					
448-012	1-1/4	25	100	040	4.24
448-015	1-1/2	25	100	040	4.43
448-020	2	10	120	040	7.86
448-025	2-1/2	10	0	040	11.56
448-030	3	10	0	040	15.12
448-040	4	6	0	040	26.56
448-050	5	5	0	040	51.44
448-060	6	8	0	040	62.76
448-080F	8	1	2	047	306.32
448-100F	10	1	2	047	622.44
448-120F	12	1	4	047	1243.71

Cap - Special Reinforced

SR Fipt - Stainless Steel Collar

448-012SR	1-1/4	25	100	046	11.30
-----------	-------	----	-----	-----	-------

Plugs

Plug

Spigot

449-003	3/8	50	700	040	2.92
449-005	1/2	50	1000	040	2.37
449-007	3/4	50	300	040	2.77
449-010	1	50	200	040	3.32
449-012	1-1/4	25	150	040	4.43
449-015	1-1/2	25	100	040	5.67
449-020	2	10	120	040	6.99
449-025	2-1/2	10	0	040	12.00
449-030	3	10	0	040	15.81
449-040	4	6	0	040	35.79
449-060	6	6	0	040	48.44
449-060F ⁴	6	1	6	047	122.60
449-080F ⁴	8	1	6	047	188.76
449-100F ⁴	10	1	0	047	433.32
449-120F ⁴	12	1	0	047	708.51
449-140F ⁴	14	1	2	047	776.73
449-160F ⁴	16	1	0	047	858.97
449-180F ⁴	18	1	0	047	1532.84
449-200F ⁴	20	1	0	047	2804.24
449-240F ⁴	24	1	0	047	3732.84

⁴ Plug fabricated using Cap and pipe spigot.

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug - Counter Sunk

Spigot

449-007CS	3/4	50	300	040	2.77
449-010CS	1	50	300	040	3.32

Plug

Mipt

450-003	3/8	50	700	040	3.18
450-005	1/2	50	300	040	2.92
450-007	3/4	50	300	040	3.13
450-010	1	50	300	040	5.12
450-012	1-1/4	25	300	040	5.40
450-015	1-1/2	25	150	040	5.77
450-020	2	10	120	040	7.46
450-025	2-1/2	10	80	040	10.36
450-030	3	10	0	040	15.67
450-040	4	6	0	040	35.38
450-060	6	6	0	040	103.74
450-080	8	6	0	040	126.77
450-080F ⁴	8	1	4	047	275.04
450-100F ⁴	10	1	3	047	548.11
450-120F ⁴	12	1	0	047	765.21

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
 2 - 1/2" - 6"-150 psi Max Internal Pressure Rating @ 73°F (23°C)
 8" - Larger & All Fabricated Sizes- 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-005	1/2	25	100	040	4.64
475-007	3/4	20	0	040	7.27
475-010	1	25	0	040	10.18
475-012	1-1/4	20	0	040	15.64
475-015	1-1/2	20	0	040	20.07
475-020	2	10	0	040	60.22
475-025	2-1/2	8	0	040	137.64
475-030	3	5	0	040	101.44
475-040	4	4	0	040	191.32
475-050F ²	5	1	3	047	746.64
475-060	6	3	0	040	404.79
475-080	8	1	0	040	651.09
475-100	10	1	0	041	2157.42
475-100F ²	10	1	0	047	1810.32

Schedule 40 Fittings Product
PVC Schedule 40 Fittings



Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye (continued)

Socket x Socket x Socket

475-120	12	1	0	041	3187.68
475-120F ²	12	1	0	047	2460.97
475-140F ²	14	1	0	047	3486.57
475-160F ²	16	1	0	047	4506.78
475-180F ²	18	1	0	047	5770.29
475-200F ²	20	1	0	047	6480.99
475-240F ²	24	1	0	047	8484.48

¹ Sized with Bushing

² Fiberglass reinforced



Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Max Internal Pressure Rating @ 73°F (23°C)
2- 1/2 - 6" - 150 psi Max Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi Max Internal Pressure Rating @ 73°F (23°C)

475-101 ¹	3/4X1/2	20	0	040	14.33
475-130 ¹	1X1/2	20	0	040	18.23
475-131 ¹	1X3/4	20	0	040	18.23
475-166 ¹	1-1/4X1/2	20	0	040	24.53
475-167 ¹	1-1/4X3/4	20	0	040	24.53
475-168 ¹	1-1/4X1	20	0	040	24.53
475-209 ¹	1-1/2X1/2	20	0	040	29.20
475-210 ¹	1-1/2X3/4	20	0	040	29.20
475-211 ¹	1-1/2X1	20	0	040	29.20
475-212 ¹	1-1/2X1-1/4	20	0	040	29.20
475-247 ¹	2X1/2	10	0	040	66.36
475-248 ¹	2X3/4	10	0	040	66.36
475-249 ¹	2X1	10	0	040	66.36
475-250 ¹	2X1-1/4	10	0	040	66.36
475-251 ¹	2X1-1/2	10	0	040	66.36
475-292 ¹	2-1/2X2	4	0	040	147.84
475-334 ¹	3X3/4	6	0	040	115.21
475-335 ¹	3X1	5	0	040	115.21
475-336 ¹	3X1-1/4	5	0	040	115.21
475-337 ¹	3X1-1/2	5	0	040	115.21
475-338 ¹	3X2	5	0	040	115.21
475-339 ¹	3X2-1/2	5	0	040	115.21
475-420	4X2	4	0	040	221.33
475-421 ¹	4X2-1/2	4	0	040	221.33
475-422 ¹	4X3	4	0	040	221.33
475-488F ²	5X3	1	4	047	593.86
475-490F ²	5X4	1	4	047	618.37
475-528 ¹	6X2	4	0	040	477.70
475-529 ¹	6X2-1/2	5	0	040	477.70
475-530 ¹	6X3	5	0	040	477.70
475-532	6X4	5	0	040	520.44
475-578F ²	8X2	1	2	047	893.84

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-579F ²	8X2-1/2	1	0	047	948.51
475-580F ²	8X3	1	2	047	971.16
475-582	8X4	2	0	040	891.51
475-582F ²	8X4	1	2	047	1001.70
475-585F ²	8X6	1	0	047	1032.09
475-621F ²	10X2	1	0	047	1074.47
475-622F ²	10X2-1/2	1	0	047	1092.93
475-623F ²	10X3	1	0	047	1151.31
475-624F ²	10X4	1	0	047	1218.34
475-626	10X6	1	0	041	1848.84
475-626F ²	10X6	1	0	047	1345.27
475-628	10X8	1	0	041	2054.29
475-628F ²	10X8	1	0	047	1439.44
475-661F ²	12X2	1	0	047	1458.49
475-663F ²	12X3	1	0	047	1493.29
475-664F ²	12X4	1	0	047	1562.82
475-666F ²	12X6	1	0	047	1570.34
475-668F ²	12X8	1	0	047	1821.10
475-670F ²	12X10	1	0	047	2082.21
475-691F ²	14X2	1	0	047	1733.79
475-693F ²	14X3	1	0	047	1876.57
475-694F ²	14X4	1	0	047	1968.01
475-696F ²	14X6	1	0	047	2217.27
475-698F ²	14X8	1	0	047	2540.63
475-700F ²	14X10	1	0	047	2838.01
475-702F ²	14X12	1	0	047	3179.67
475-751F ²	16X2	1	0	047	2014.38
475-753F ²	16X3	1	0	047	2177.57
475-754F ²	16X4	1	0	047	2264.54
475-756F ²	16X6	1	0	047	2548.36
475-758F ²	16X8	1	0	047	2902.12
475-760F ²	16X10	1	0	047	3229.99
475-762F ²	16X12	1	0	047	3599.37
475-764F ²	16X14	1	0	047	4073.99
475-781F ²	18X2	1	0	047	2197.88
475-783F ²	18X3	1	0	047	2298.47
475-784F ²	18X4	1	0	047	2332.62
475-786F ²	18X6	1	0	047	4469.12
475-788F ²	18X8	1	0	047	3335.41
475-790F ²	18X10	1	0	047	3709.93
475-792F ²	18X12	1	0	047	4303.89
475-794F ²	18X14	1	0	047	4725.42
475-796F ²	18X16	1	0	047	4955.86
475-811F ²	20X2	1	0	047	2311.11
475-813F ²	20X3	1	0	047	2504.47
475-814F ²	20X4	1	0	047	2536.92
475-816F ²	20X6	1	0	047	2584.51
475-818F ²	20X8	1	0	047	3493.64
475-820F ²	20X10	1	0	047	3883.89
475-822F ²	20X12	1	0	047	4680.68
475-824F ²	20X14	1	0	047	5238.27
475-826F ²	20X16	1	0	047	5806.08
475-828F ²	20X18	1	0	047	6232.33
475-901F ²	24X2	1	0	047	2917.27



Schedule 40 Fittings Product PVC Schedule 40 Fittings

Wyes

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Wye - Reducing (continued)

Socket x Socket x Socket

475-903F ²	24X3	1	0	047	2981.46
475-904F ²	24X4	1	0	047	3063.63
475-906F ²	24X6	1	0	047	5392.31
475-908F ²	24X8	1	0	047	5882.18
475-910F ²	24X10	1	0	047	5944.30
475-912F ²	24X12	1	0	047	6292.26
475-914F ²	24X14	1	0	047	6508.14
475-916F ²	24X16	1	0	047	6815.60
475-918F ²	24X18	1	0	047	7409.38
475-920F ²	24X20	1	0	047	8099.07

¹ Sized with Bushing

² Fiberglass reinforced



Double Wye

Socket x Socket x Socket x Socket

100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-020F ²	2	1	4	047	467.62
476-030F ²	3	1	3	047	770.20
476-040F ²	4	1	2	047	857.96
476-060F ²	6	1	0	047	977.04
476-080F ²	8	1	0	047	1189.88
476-100F ²	10	1	0	047	2181.91
476-120F ²	12	1	0	047	2597.59
476-140F ²	14	1	0	047	3780.54

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.



Double Wye - Reducing

Socket x Socket x Socket x Socket

Size 3" is 150 psi, all Fabricated Sizes- 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)

476-338	3X2	5	0	040	169.10
476-420F ²	4X2	1	4	047	759.53
476-421F ²	4X2-1/2	1	2	047	792.46
476-422F ²	4X3	1	3	047	815.26
476-528F ²	6X2	1	2	047	764.87
476-529F ²	6X2-1/2	1	2	047	832.66
476-530F ²	6X3	1	2	047	865.40
476-532F ²	6X4	1	0	047	878.92
476-578F ²	8X2	1	2	047	933.09
476-579F ²	8X2-1/2	1	0	047	970.18
476-580F ²	8X3	1	0	047	1044.02
476-582F ²	8X4	1	0	047	1057.47
476-585F ²	8X6	1	0	047	1108.59
476-621F ²	10X2	1	0	047	1390.20
476-622F ²	10X2-1/2	1	0	047	1472.92

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Double Wye - Reducing (continued)

Socket x Socket x Socket x Socket

476-623F ²	10X3	1	0	047	1515.14
476-624F ²	10X4	1	0	047	1664.78
476-626F ²	10X6	1	0	047	1867.37
476-628F ²	10X8	1	0	047	1947.30
476-661F ²	12X2	1	0	047	1983.41
476-662F ²	12X2 1/2	1	0	047	2005.91
476-663F ²	12X3	1	0	047	2113.57
476-664F ²	12X4	1	0	047	2154.84
476-666F ²	12X6	1	0	047	2277.11
476-668F ²	12X8	1	0	047	2335.53
476-670F ²	12X10	1	0	047	2474.27
476-756F ²	16X6	1	0	047	4157.49
476-786F ²	18X6	1	0	047	2329.12

² Fiberglass reinforced

For larger sizes please contact your Regional Spears® Distribution Center.

Unions



Union - Socket/Buna

Socket x Socket with Buna-N O-ring Seal

150 psi @ 73°F (23°C)

457-005	1/2	20	120	040	10.60
457-007	3/4	15	90	040	12.04
457-010	1	10	60	040	12.41
457-012	1-1/4	5	30	040	39.99
457-015	1-1/2	5	20	040	41.63
457-020	2	5	0	040	56.16
457-025	2-1/2	5	0	040	78.60
457-030	3	5	0	040	125.58
457-040	4	4	0	040	173.89
457-060	6	1	0	040	386.38

Union - Socket/EPDM

Socket x Socket with EPDM O-ring Seal

150 psi @ 73°F (23°C)

497-005	1/2	20	120	040	11.66
497-007	3/4	15	90	040	13.33
497-010	1	10	60	040	13.62
497-012	1-1/4	5	30	040	43.98
497-015	1-1/2	5	20	040	45.84
497-020	2	5	0	040	61.81
497-025	2-1/2	5	0	040	86.51
497-030	3	5	0	040	137.99
497-040	4	4	0	040	185.66
497-060	6	1	0	040	412.56

