



Schedule 80 PVC Product PVC Schedule 80 Fittings

Caps

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Cap - Special Reinforced (continued)

SR Fipt - Stainless Steel Collar

848-005SR	1/2	50	300	086	9.21
848-007SR	3/4	25	300	086	11.81
848-030SR	3	5	0	086	72.80

Plugs

Plug

Spigot

849-005	1/2	50	300	080	11.43
849-007	3/4	50	300	080	12.72
849-010	1	50	200	080	14.34
849-012	1-1/4	25	100	080	18.34
849-015	1-1/2	10	120	080	20.08
849-020	2	10	120	080	26.61
849-025F ⁴	2-1/2	4	0	083	62.30
849-030F ⁴	3	4	0	083	75.11
849-040F ⁴	4	4	0	083	164.28
849-060F ⁴	6	1	6	083	456.77
849-080F ⁴	8	1	6	083	594.74
849-100F ⁴	10	1	2	083	967.08
849-120F ⁴	12	1	0	083	1791.51
849-140F ⁴	14	1	0	083	2071.70
849-160F ⁴	16	1	0	083	2454.99
849-180F ⁴	18	1	0	083	3423.03
849-200F ⁴	20	1	0	084	5551.09
849-240F ⁴	24	1	0	083	10692.54

⁴ Plug fabricated using Cap and pipe spigot.

Plug

Mipt

850-002	1/4	50	900	080	13.21
850-003	3/8	50	600	080	13.21
850-005	1/2	50	500	080	11.78
850-007	3/4	50	300	080	12.22
850-010	1	25	150	080	14.98
850-012	1-1/4	10	120	080	22.11
850-015	1-1/2	10	120	080	26.86
850-020	2	10	120	080	27.58
850-025	2-1/2	5	60	080	77.00
850-030	3	5	40	080	89.83
850-040	4	6	0	080	174.89
850-060	6	6	0	080	207.91
850-080	8	6	0	080	300.97
850-080F ⁴	8	1	2	083	513.20
850-100F ⁴	10	1	3	083	752.11
850-120F ⁴	12	1	0	083	1030.19

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Plug (continued)

Mipt

⁴ Plug fabricated using Cap and threaded pipe.

Wyes

Wye

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - 10" & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 12" 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-005	1/2	25	100	080	28.59
875-007	3/4	25	0	080	30.06
875-010	1	20	0	080	48.07
875-012	1-1/4	20	0	080	73.73
875-015	1-1/2	20	0	080	73.73
875-020	2	10	0	080	211.51
875-025	2-1/2	6	0	080	522.49
875-030	3	5	0	080	679.96
875-040	4	4	0	080	842.49
875-050F ²	5	1	2	083	1317.99
875-060	6	2	0	080	1150.68
875-080	8	1	0	080	2314.10
875-080F ²	8	1	0	083	1783.11
875-100F ²	10	1	0	083	2798.07
875-120F ²	12	1	0	083	3556.43
875-140F ²	14	1	0	083	5939.77
875-160F ²	16	1	0	083	7802.58
875-180F ²	18	1	0	083	8747.78
875-200F ²	20	1	0	083	11685.36
875-240F ²	24	1	0	083	15551.71

¹ Sized with Bushing

² Fiberglass reinforced

Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 8" - 10" & All Fabricated Sizes - 100 psi Maximum Internal Pressure Rating @ 73°F (23°C)
 12" 80 psi Maximum Internal Pressure Rating @ 73°F (23°C)

875-101 ¹	3/4X1/2	25	0	080	34.69
875-130 ¹	1X1/2	20	0	080	60.82
875-131 ¹	1X3/4	20	0	080	60.82
875-166 ¹	1-1/4X1/2	20	0	080	93.69
875-167 ¹	1-1/4X3/4	20	0	080	93.69