



STORE+®

60" x 32" Vikrell® bath/shower with Aging in Place backerboards, right drain 71420126



Features

- Adjustable corner shelves maximize showering space
- Includes four rimmed shelves, two caddies, two soap dishes With towel bars, and two hooks
- Dishwasher-safe shelves and bins snap into place; no tools required
- Shaving ledge/footrest for added comfort
- Durable high-gloss finish provides a smooth, shiny surface that is easy to clean
- Caulk-free four-piece modular design made of solid Vikrell® material
- Factory-installed Aging in Place backerboards for future grab bar installation
- Innovative Dry-Block™ seal and channeled water containment system form watertight seams

Recommended Products/Accessories

K-23726 Drain treatment

Included Components

71121120 60" x 32" Vikrell® bath, right drain



Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662
HUD, UM Bulletin 73
EPA TSCA Title VI/CARB P2

Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® MaterialSTERLING® Warranty - Bathing & Showering Accessories

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------


	0	White
---	---	-------

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.sterlingplumbing.com.

3-31-2025 01:16 - US/CA



Technical Information

All product dimensions are nominal.

Drain location:	Right
Basin area, bottom:	42" x 20" (1067 mm x 508 mm)
Basin area, top:	54" x 26" (1372 mm x 660 mm)
Water depth:	13-3/4" (349 mm)
Water capacity:	55 gal (208.2 L)
Minimum flat for door:	3" (76 mm)
Maximum door height:	59" (1499 mm)
Maximum door width:	57-11/16" (1465 mm)

Notes

Install this product according to the installation instructions.

Studs should be positioned roughly as shown.

Double studding is recommended for pivot shower door installations.

Attach grab bars at the specified backer board locations only.