

Plus Two Multi-Purpose Valve

Horizontal or Vertical installation

GPM: 20 - 10,000
SIZES: 1-1/2" — 14"



Five (5) Valves in one:

- Shut-off valve
- Flow Control Valve (Globe Style)
- Non slam check valve
- Flow Metering Valve
- Straight Pattern Valve can be converted to a right angle pattern valve

Low pressure drop (Equal to or better than any comparable valve on the market today)

Suitable for 125 and 250 PSI W.P.

Suction Diffuser Rear Strainer Pullout (RSP)

Suitable for 125 & 250 PSI W.P.

GPM: 20 - 10,000
SIZES: 1-1/2" — 16"



Integral cast straightening vane design ensures uniform flow to the suction inlet of the pump

Oversized Body Cylinder ensures minimal pressure drop

Removable Cover Plate and reusable "O" ring allows for easy access and maintenance of Permanent Strainer

Blow Down port allows for routine maintenance and removal of sediment and debris

Optional Magnetic Insert to trap small metallic particles

Specifically designed to serve the needs of commercial HVAC and industrial applications.

Accu-Flo Balancing Valve

Fixed Port Venturi Balancing Valve

GPM: 1/2 - 1000
SIZES: 1/2" — 4"



Flow measurement independent of stem and ball position.

Modified venturi flow measurement section ensures precise and consistent differential pressure readings.

Positive shut-off ball valve for service work.

Can be installed in any position

Tamper resistant memory stop

1/2" – 2" available in sweat and NPT connections.

2-1/2", 3" and 4" available flanged connections.