

## Onix Fittings



**SelfTite™ Clamps** — Pretensioned for easy field installation. The chrome-vanadium spring steel maintains a constant tension on the Onix under all operating conditions. SelfTites incorporate a zinc coating to guard against corrosion.

| Description                 | QTY | Model#    | Order#   | lbs. |
|-----------------------------|-----|-----------|----------|------|
| 3/8" SelfTite Clamp (19 mm) | 10  | 663019-10 | 81000523 | 3    |
| 1/2" SelfTite Clamp (22 mm) | 10  | 663022-10 | 81000526 | 4    |
| 5/8" SelfTite Clamp (25 mm) | 10  | 663025-10 | 81000529 | 4    |
| 3/4" SelfTite Clamp (29 mm) | 10  | 663029-10 | 81000532 | 5    |

**TorqueTite™ Clamps** — our best stainless steel screw clamps.

| Description                      | QTY | Model#     | Order#   | lbs. |
|----------------------------------|-----|------------|----------|------|
| 3/8" TorqueTite Clamp (17–19 mm) | 10  | 6641117-10 | 81002913 | 2    |
| 1/2" TorqueTite Clamp (21–23 mm) | 10  | 6641524-10 | 81002916 | 2    |
| 5/8" TorqueTite Clamp (25–27 mm) | 10  | 6641928-10 | 81002919 | 2    |
| 3/4" TorqueTite Clamp (29–31 mm) | 10  | 6642232-10 | 81002922 | 2    |

The Onix **TorqueTite** is a rugged, stainless steel clamp capable of withstanding large pressures and temperatures while being easy to install. Do not overtighten!

**SST20 Onix Swivel Fittings** — for Stainless Steel, and Custom Tubular Manifolds.

| Description                         | QTY | Model#    | Order#   | lbs. |
|-------------------------------------|-----|-----------|----------|------|
| 3/8" Onix x 3/4" BSP Swivel Fitting | 10  | 689001-10 | 81000679 | 1    |
| 1/2" Onix x 3/4" BSP Swivel Fitting | 10  | 689002-10 | 81000681 | 1    |
| 5/8" Onix x 3/4" BSP Swivel Fitting | 10  | 689003-10 | 81000683 | 2    |
| 3/4" Onix x 3/4" BSP Swivel Fitting | 10  | 689004-10 | 81000684 | 2    |

Use these female **Onix SST20** Fittings to connect Onix to our Stainless Steel manifolds. Order Onix SelfTite or TorqueTite clamps separately. BSP threads are not compatible with NPT.



**Onix Barb x Male Sweat Fittings** — for transitioning Onix to sweat fittings.

| Description                         | QTY | Model#    | Order#   | lbs. |
|-------------------------------------|-----|-----------|----------|------|
| 3/8" Onix x 1/2" Male Sweat Adapter | 10  | 684001-10 | 81000659 | 1    |
| 1/2" Onix x 1/2" Male Sweat Adapter | 10  | 685001-10 | 81000663 | 1    |
| 5/8" Onix x 1/2" Male Sweat Adapter | 10  | 686001-10 | 81000667 | 1    |
| 3/4" Onix x 3/4" Male Sweat Adapter | 10  | 687001-10 | 81000671 | 2    |

Sweat **Onix Barbs** into copper tees or ball valves for easy field manifold construction



**Onix Sweat Elbow Fittings** — for connecting Onix supply lines to baseboard, fan coils, or kick space heaters.

| Description                   | QTY | Model#    | Order#   | lbs. |
|-------------------------------|-----|-----------|----------|------|
| 1/2" Onix x 3/4" Female Sweat | 10  | 185074-10 | 81000116 | 3    |
| 5/8" Onix x 3/4" Female Sweat | 10  | 185625-10 | 81000120 | 3    |
| 3/4" Onix x 3/4" Female Sweat | 10  | 185075-10 | 81000118 | 3    |

Use these all brass **Onix Elbow Fittings** to make transitions to baseboards, radiators, or fan coils when using Onix as supply/return piping.

