

BIG BUBBLE GAS LEAK DETECTOR SPRAY FORMULA LDS-SPEC

PRODUCT DESCRIPTION

PRODUCT

BIG BUBBLE Gas Leak Detector, Spray Formula

TYPE

BIG BUBBLE is a noncorrosive, nonfreezing, nontoxic, non-soap base, iridescent blue leak detector.

Will not cause corrosion or deterioration of metal, copper, brass or plastic.

RECOMMENDED USES

BIG BUBBLE Gas Leak Detector is for use on all types of connections on gas lines, air lines, gas cylinders, refrigeration condensers, evaporators, air pumps, tanks used for storing gases or any system carrying gaseous products.

BIG BUBBLE'S water soluble polymer detects large and small leaks by forming bubbles which remain for up to 10 minutes.

Not recommended for oxygen systems.

TEMPERATURE RANGE USE

-10°F (-23°C) to 212°F (100°C)

COLOR/CONSISTENCY

Iridescent Blue Liquid

U.S. FEDERAL SPECIFICATIONS

Meets Federal Specification
MIL-L-25567-C.

ASTM SPECIFICATIONS

Meets ASTM G188-05

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
Plastic Container w/ Sprayer (Display Box)	
LDS	Pint (237 ml)
Plastic Container	
LDS16	Pint (237 ml)
Plastic Container w/ Sprayer	
LDS32	Quart (.95 L)
Plastic Jug w/ Spout	
LDS1	Gallon (3.785 L)
Plastic Pail w/ Handle	
LDS5	5 Gallon (18.9 L)
55 Gallon Drum	
LDS55	55 Gallon (208 L)

WEIGHT PER U.S. GALLON

8.41 lbs. (3.8 kg) ±0.2

SHIPPING WEIGHT PER CASE

<u>Stock Code</u>	<u>Case Weight</u>	<u>#/Case</u>
LDS	16 lbs. (7.3 kg)	12
LDS16	15 lbs. (6.8 kg)	12
LDS32	31 lbs. (14.1 kg)	12
LDS1	55 lbs. (24.9 kg)	6
LDS5	42 lbs. (19.1 kg)	1
LDS55	502 lbs. (227.7 kg)	1

DIRECTIONS FOR USE

1. Apply liberal amounts of **BIG BUBBLE** Gas Leak Detector by spraying the area where the leak is suspected.
2. The slightest pressure leak will cause bubbles to form and remain for up to 10 minutes.

KEEP OUT OF REACH OF CHILDREN.

SEE SAFETY DATA SHEET (SDS) FOR COMPLETE PRECAUTIONS FOR SAFE HANDLING AND USE.

MADE IN THE U.S.A.

LDS-SPEC

© 2022 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.

The information contained in this bulletin is correct to the best of our knowledge. The recommendations or suggestions herein are made without guarantee or representation as to result, since the conditions of use are beyond our control. We suggest that you evaluate the recommendations contained in this bulletin. No statement is to be construed as violating any copyright or patent. They are intended only as a source of information.



The Industry Standard for Over 100 Years

P.O. Box 380 • Wadsworth, OH 44282 U.S.A.
Phone: 1-330-334-2524 • FAX 1-330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com