

IOWA® hydrants are intended for irrigation purposes and used for filling field spray equipment, cleaning tools and equipment, lawn and garden care, watering livestock - immediate water flow even in sub zero temperatures.

Specifications:

Female Inlet: Model Y34 - ¾" NPT
Model Y1 - 1" NPT

Casing: Model Y34 - 1" Galvanized Steel Pipe
Model Y1 - 1¼" Galvanized Steel Pipe

Operating Rod: ¾" Galvanized Steel Pipe

Drain Hole: Tapped - ⅛" N.P.T.

Removable Nozzle: ¾" Brass Male Hose Nozzle

Optional At Additional Cost:

- 1" Brass Pipe Outer Casing
- ¾" Brass Pipe Operating Pipe
- Y34 ONLY:
 - 1" Stainless Steel Outer Casing
 - ¾" Stainless Steel Operating Pipe
 - 1" NPSH Hose Nozzle

Features:

- **Adjustable Link** - Provides easy and positive adjustment of the lever lock tension.
- **Rod Guide** - Eliminates side pull on rod, reduces wear on packing, packing nut & stem.
- **Flow Finder and Lock** - A simple cam that can be set to automatically obtain the same flow each time or lock against accidental opening.
- **Long Life Packing** - Graphite packing for lubricity and long life.
- **One Piece Variable Flow Plunger** - Large cushion type seal for longer life - is not easily damaged and assures shut-off even when foreign particles are present. Automatic drain feature - plunger opens drain to prevent freezing - closes at any flow to prevent wasting water.
- **Maintenance & Repair** - Woodford has manufactured the IOWA® hydrant since 1929, and although many improvements have been made through the years, all parts are interchangeable. All repairs can be made from top of unit without removing hydrant from the ground.
- **Maximum Working Pressure:** 125 p.s.i.
- **Maximum Temperature:** 120° F

SHIPPING WEIGHT

Bury Depth (Ft)	1	2	3	4	5	6*	7*
Model Y34 (Lbs)	15	17	19	22	24	26	28
Model Y1 (Lbs)	18	20	22	25	28	31	34



*Must ship by truck line due to length.

For Installation / Troubleshooting Instructions go to www.woodfordmfg.com or call 1-800-621-6032




Freezeless IOWA® Yard Hydrant Model Y34 & Y1

Galvanized Steel Pipe Standard
Optional Add SS - Stainless Steel
Optional Add BR - Brass



When ordering, specify model and bury depth.



MODEL Y34 & Y1 PARTS LIST

ITEM	PART#	DESCRIPTION	ITEM	PART#	DESCRIPTION
	RK-Y34HA	Repair Kit Y34 Head Assembly (Includes Items 1, 3-16) Replaces Part 15003	22	Y34 & Y1 OPERATING PIPE (Bury Depth & Length)	
	RK-Y1HA	Repair Kit Y1 Head Assembly (Includes Items 2, 3-15 & 17) Replaces Part 15001		10023	1' Bury (35 1/2" Long)
1	15004	Y34 Head with 3/4" Nozzle		10024	2' Bury (47 1/2" Long)
2	15002	Y1 Head with 3/4" Nozzle		10025	3' Bury (59 1/2" Long)
3	10100	Packing Nut		10026	4' Bury (71 1/2" Long)
4	10101	Packing		10027	5' Bury (83 1/2" Long)
5	10102	Packing Support Washer		10028	6' Bury (95 1/2" Long)
6	10104	Brass Rod Stem		10029	7' Bury (107 1/2" Long)
7	10011	Reducing Coupling		10030	8' Bury (119 1/2" Long)
8	10206	Hex Nut (3)		10089	9' Bury (131 1/2" Long)
9	10009	Upper Link		10090	10' Bury (143 1/2" Long)
10	15007	Lower Link (Includes Item 11)	22	Y34 ONLY Stainless Steel OPERATING PIPE	
11	10019	Set Screw (2)		10123	1' Bury (35 1/2" Long)
12	15008	Cam & Clevis Assembly		10124	2' Bury (47 1/2" Long)
13	10020	Link Bolt (2)		10125	3' Bury (59 1/2" Long)
14	10021	Lever Bolt		10126	4' Bury (71 1/2" Long)
15	10008	Lever		10127	5' Bury (83 1/2" Long)
16	10004	3/4" Brass Hose Nozzle (Standard)		10128	6' Bury (95 1/2" Long)
17	10007	1" Brass Hose Nozzle (Optional)		10129	7' Bury (107 1/2" Long)
18	10105	Y34 Plunger		10130	8' Bury (119 1/2" Long)
19	10018	Y34 Valve Body (3/4" NPT Inlet)		10131	9' Bury (131 1/2" Long)
20	10106	Y1 Plunger		10132	10' Bury (143 1/2" Long)
21	10017	Y1 Valve Body (1" NPT Inlet)		RK-Y34	Repair Kit (Includes Items 3-6 & 18)
				RK-Y1	Repair Kit (Includes Items 3-6 & 20)
				RK-YHL	Repair Kit (Includes Items 8-14)

For more information contact...

WOODFORD MANUFACTURING COMPANY

2121 Waynoka Road, Colorado Springs, Colorado 80915 • Phone: (800) 621-6032 • Fax: (800) 765-4115

To view our complete product line visit: www.woodfordmfg.com or email: sales@woodfordmfg.com